



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**10757**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (7 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0104032</b>	GFL0091187	GFL0082190
Sample Date		Client Info		<b>19 Feb 2024</b>	06 Oct 2023	23 Jun 2023
Machine Age	hrs	Client Info		<b>52047</b>	17363	17036
Oil Age	hrs	Client Info		<b>17968</b>	17363	17036
Filter Age	hrs	Client Info		<b>650</b>	650	650
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>27</b>	18	12
Chromium	ppm	ASTM D5185m	>20	<b>1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	3	4
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m	>330	<b>2</b>	<1	<1
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>7</b>	4	4
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	3	2
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.7</b>	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.4</b>	7.9	8.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.7</b>	20.2	19.5
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	4	2
Boron	ppm	ASTM D5185m	0	<b>19</b>	22	50
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>77</b>	63	77
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>741</b>	838	418
Calcium	ppm	ASTM D5185m	1070	<b>1806</b>	1240	1758
Phosphorus	ppm	ASTM D5185m	1150	<b>1000</b>	942	1044
Zinc	ppm	ASTM D5185m	1270	<b>1509</b>	1182	1272
Sulfur	ppm	ASTM D5185m	2060	<b>3652</b>	2999	4383
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.5</b>	16.2	15.2
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>6.0</b>	8.5	8.5
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.8</b>	13.7	14.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0104032  
**Lab Number** : 06104202  
**Unique Number** : 10902432  
**Test Package** : FLEET

**Received** : 29 Feb 2024  
**Tested** : 01 Mar 2024  
**Diagnosed** : 01 Mar 2024 - Wes Davis

**GFL Environmental - 015 - Columbia**  
 7800 Farrow Road  
 Columbia, SC  
 US 29203-3219  
 Contact: NOEL MATTHEWS  
 nmatthewsjr@gflenv.com  
 T: (803)935-0249  
 F: (803)935-0244

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)