



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 210G 1FF210GXHMF529661
 Component
Right Final Drive
 Fluid
JOHN DEERE GL-5 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0202738	JR0190867	JR0133195
Sample Date		Client Info		27 Feb 2024	29 Oct 2023	14 Jul 2022
Machine Age	hrs	Client Info		2500	2058	507
Oil Age	hrs	Client Info		442	2058	507
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	293	122	329
Iron	ppm	ASTM D5185m	>750	313	260	352
Chromium	ppm	ASTM D5185m	>9	5	4	7
Nickel	ppm	ASTM D5185m	>10	1	1	0
Titanium	ppm	ASTM D5185m		1	<1	<1
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>40	15	2	2
Lead	ppm	ASTM D5185m	>15	0	0	0
Copper	ppm	ASTM D5185m	>40	0	1	2
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		<1	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	64	19	21
Potassium	ppm	ASTM D5185m	>20	4	4	0
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	LIGHT	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<1	1	0
Boron	ppm	ASTM D5185m		10	22	42
Barium	ppm	ASTM D5185m		0	3	12
Molybdenum	ppm	ASTM D5185m		<1	1	<1
Manganese	ppm	ASTM D5185m		4	3	6
Magnesium	ppm	ASTM D5185m		0	4	0
Calcium	ppm	ASTM D5185m		23	13	15
Phosphorus	ppm	ASTM D5185m		515	641	464
Zinc	ppm	ASTM D5185m		11	18	29
Sulfur	ppm	ASTM D5185m		17554	20103	15941
Visc @ 40°C	cSt	ASTM D445		127	148	185



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0202738 **Received** : 29 Feb 2024
Lab Number : 06104552 **Tested** : 01 Mar 2024
Unique Number : 10902782 **Diagnosed** : 04 Mar 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

JRE - GARNER
 4161 AUBURN CHURCH RD
 GARNER, NC
 US 27529
 Contact: RALEIGH SHOP
 sean.betts@jamesriverequipment.com; catherine.anastasio@wearcheck.com
 T: (919)614-2260
 F: (919)779-5432

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)