



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION

Area
Store 3 - Norton
Machine Id
JOHN DEERE 853M 1T0853MXAKF343716
Component
Left Propel Gearbox
Fluid
JOHN DEERE GL-5 80W90 (2 GAL)

RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0045184	LEC0042716	LEC0038535
Sample Date		Client Info		27 Feb 2024	30 Aug 2023	20 Feb 2023
Machine Age	hrs	Client Info		3050	2577	2083
Oil Age	hrs	Client Info		473	494	507
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ATTENTION	ABNORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		172	131	182
Iron	ppm	ASTM D5185m	>1250	321	323	314
Chromium	ppm	ASTM D5185m	>10	4	5	3
Nickel	ppm	ASTM D5185m	>10	<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	2	2
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m		8	11	25
Lead	ppm	ASTM D5185m		<1	<1	0
Copper	ppm	ASTM D5185m		3	4	6
Tin	ppm	ASTM D5185m		0	1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m		37	42	109
Potassium	ppm	ASTM D5185m	>20	<1	3	6
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is lower than normal. This plus the additive levels indicates the addition of a different brand, or type of oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		1	1	<1
Boron	ppm	ASTM D5185m		1	2	4
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	1	<1
Manganese	ppm	ASTM D5185m		1	2	3
Magnesium	ppm	ASTM D5185m		92	106	101
Calcium	ppm	ASTM D5185m		3195	3375	3309
Phosphorus	ppm	ASTM D5185m		961	984	899
Zinc	ppm	ASTM D5185m		1146	1217	1076
Sulfur	ppm	ASTM D5185m		3148	4038	3596
Visc @ 40°C	cSt	ASTM D445		52.8	52.5	53.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0045184 **Received** : 29 Feb 2024
Lab Number : 06104581 **Tested** : 01 Mar 2024
Unique Number : 10902811 **Diagnosed** : 04 Mar 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com
 T:
 F: (740)373-5570

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)