



Machine Id
923012-565

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (28 QTS)

RECOMMENDATION

We advise that you check the fuel injection system. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0110280	GFL0102811	GFL0090465
Sample Date		Client Info		27 Feb 2024	01 Dec 2023	19 Oct 2023
Machine Age	hrs	Client Info		23205	22829	22625
Oil Age	hrs	Client Info		580	22625	580
Filter Age	hrs	Client Info		580	204	580
Oil Changed		Client Info		Changed	Not Changed	Changed
Filter Changed		Client Info		Changed	Not Changed	Changed
Sample Status				SEVERE	MARGINAL	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	58	23	68
Chromium	ppm	ASTM D5185m	>20	3	1	2
Nickel	ppm	ASTM D5185m	>2	0	<1	0
Titanium	ppm	ASTM D5185m	>2	0	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	3	2	2
Lead	ppm	ASTM D5185m	>40	1	<1	2
Copper	ppm	ASTM D5185m	>330	2	1	10
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Silicon	ppm	ASTM D5185m	>25	7	5	8
Potassium	ppm	ASTM D5185m	>20	1	<1	1
Fuel	%	ASTM D3524	>3.0	▲ 7.9	▲ 3.1	▲ 7.2
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	1.3	0.6	1.4
Nitration	Abs/cm	*ASTM D7624	>20	10.5	7.2	10.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.3	18.8	21.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

Sodium	ppm	ASTM D5185m		11	7	26
Boron	ppm	ASTM D5185m	0	7	6	2
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	55	60	61
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	800	890	914
Calcium	ppm	ASTM D5185m	1070	947	1037	1046
Phosphorus	ppm	ASTM D5185m	1150	936	1014	940
Zinc	ppm	ASTM D5185m	1270	1107	1227	1185
Sulfur	ppm	ASTM D5185m	2060	2515	2978	2487
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.7	13.7	17.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.4	8.4	6.6
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 11.5	12.6	▲ 12.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0110280 **Received** : 29 Feb 2024
Lab Number : 06105077 **Tested** : 04 Mar 2024
Unique Number : 10903307 **Diagnosed** : 04 Mar 2024 - Wes Davis
Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

GFL Environmental - 622 - Traverse City Hauling
 160 Hughes Dr
 Traverse City, MI
 US 49686
 Contact: GARY BREWER

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: