



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
AMR-St Louis
 Machine Id
574183 SENNEBOGEN 840M 85001185
 Component
Front Right Final Drive
 Fluid
SHELL SPIRAX HD 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DJJ0020771	DJJ0020673	DJJ0012564
Sample Date		Client Info		29 Jan 2024	13 Oct 2023	14 Jul 2023
Machine Age	hrs	Client Info		9415	8892	8358
Oil Age	hrs	Client Info		1000	500	1000
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	<1	33	35
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	0	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	0	<1	1
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<1	<1	<1
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	2	<1
Boron	ppm	ASTM D5185m	234	253	267	321
Barium	ppm	ASTM D5185m	0.1	0	3	1
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	0.0	0	<1	<1
Calcium	ppm	ASTM D5185m	0.4	2	10	8
Phosphorus	ppm	ASTM D5185m	864	1060	956	997
Zinc	ppm	ASTM D5185m	0.6	0	4	6
Sulfur	ppm	ASTM D5185m	16893	21030	18293	21296
Visc @ 40°C	cSt	ASTM D445	139	133	161	161



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DJJ0020771
Lab Number : 06105553
Unique Number : 10903783
Test Package : MOBCE

Received : 29 Feb 2024
Tested : 02 Mar 2024
Diagnosed : 02 Mar 2024 - Wes Davis

ADVANTAGE METALS RECYCLING - ST LOUIS
 5 N MARKET
 ST LOUIS, MO
 US 63102
 Contact: JEANETTE VAGO
 jeanette.vago@advantagerecycling.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: