



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 50G 45 (S/N 1FF050GXJMH294005)

Component
Diesel Engine

Fluid
MOBIL 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0158795	JR0129467	JR0129682
Sample Date		Client Info		16 Feb 2024	19 Jan 2023	18 Oct 2022
Machine Age	hrs	Client Info		1428	832	796
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	15	3	10
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	3	<1	2
Lead	ppm	ASTM D5185m	>26	1	<1	<1
Copper	ppm	ASTM D5185m	>26	<1	<1	2
Tin	ppm	ASTM D5185m	>4	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	6	4	7
Potassium	ppm	ASTM D5185m	>20	2	2	11
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.1	0.2
Nitration	Abs/cm	*ASTM D7624	>20	7.7	5.1	7.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.2	18.1	21.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>118	2	1	<1
Boron	ppm	ASTM D5185m		4	7	12
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		60	56	63
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		967	896	884
Calcium	ppm	ASTM D5185m		1271	1181	1225
Phosphorus	ppm	ASTM D5185m		1127	994	1036
Zinc	ppm	ASTM D5185m		1325	1238	1229
Sulfur	ppm	ASTM D5185m		3998	4070	3883
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.6	13.5	16.8
Base Number (BN)	mg KOH/g	ASTM D2896		9.7	10.3	11.2
Visc @ 100°C	cSt	ASTM D445		13.1	13.2	13.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0158795 **Received** : 18 Mar 2024
Lab Number : 06121391 **Tested** : 19 Mar 2024
Unique Number : 10930224 **Diagnosed** : 19 Mar 2024 - Wes Davis
Test Package : MOBCE (Additional Tests: TBN)

HALEY CHISHOLM AND MORRIS INC
 3316 EARLYSVILLE RD
 EARLYSVILLE, VA
 US 22936
 Contact: H SAWYER
 HSAWYERHCM@GMAIL.COM
 T: (434)996-2189
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)