



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
7282
Component
Diesel Engine
Fluid
SHELL 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0854005	WC0800664	WC0767589
Sample Date		Client Info		22 Feb 2024	28 Apr 2023	21 Dec 2022
Machine Age	mls	Client Info		101929	92758	88137
Oil Age	mls	Client Info		9187	4823	12500
Filter Age	mls	Client Info		9187	4823	12500
Oil Changed		Client Info		Changed	N/A	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	27	16	23
Chromium	ppm	ASTM D5185m	>20	1	<1	0
Nickel	ppm	ASTM D5185m	>4	<1	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	15	8	11
Lead	ppm	ASTM D5185m	>40	<1	0	0
Copper	ppm	ASTM D5185m	>330	1	<1	<1
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	7	4	0
Potassium	ppm	ASTM D5185m	>20	8	6	11
Fuel		WC Method	>5	<1.0	1.4	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	0.3	0.5
Nitration	Abs/cm	*ASTM D7624	>20	9.4	7.3	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.6	17.6	21.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	2	<1
Boron	ppm	ASTM D5185m		18	118	115
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		19	72	78
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	470	121	388	264
Calcium	ppm	ASTM D5185m	1150	2328	1777	1879
Phosphorus	ppm	ASTM D5185m	94	1051	988	1008
Zinc	ppm	ASTM D5185m	1030	1205	1240	1222
Sulfur	ppm	ASTM D5185m		4119	3595	3738
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.0	14.3	16.0
Base Number (BN)	mg KOH/g	ASTM D2896	7.17	5.9	7.0	7.8
Visc @ 100°C	cSt	ASTM D445	10.90	13.3	12.4	12.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WC0854005

Lab Number : 06121477

Unique Number : 10930310

Test Package : FLEET

Received : 18 Mar 2024

Tested : 19 Mar 2024

Diagnosed : 21 Mar 2024 - Jonathan Hester

CARCO TRANSPORTATION

3403 EAST ROOSEVELT ROAD

LITTLE ROCK, AR

US 72206

Contact: DENNIS CATES

denniscates@carcotrans.com

T: (800)967-0777

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)