



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
ISUZU 846-4448
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (11 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0017937	RPL0016334	RPL0012031
Sample Date		Client Info		07 Mar 2024	16 Nov 2023	16 Mar 2023
Machine Age	mls	Client Info		105372	101267	89459
Oil Age	mls	Client Info		8117	4012	0
Filter Age	mls	Client Info		8117	4012	0
Oil Changed		Client Info		Not Changd	Filtered	Not Changd
Filter Changed		Client Info		Not Changd	Changed	None
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	31	10	13
Chromium	ppm	ASTM D5185m	>20	<1	0	<1
Nickel	ppm	ASTM D5185m	>4	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	2	2
Lead	ppm	ASTM D5185m	>40	<1	0	0
Copper	ppm	ASTM D5185m	>330	2	<1	<1
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	7	3	5
Potassium	ppm	ASTM D5185m	>20	3	0	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1	0.6	0.6
Nitration	Abs/cm	*ASTM D7624	>20	9.9	7.4	8.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.2	20.2	20.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	2	2
Boron	ppm	ASTM D5185m	0	3	<1	6
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	64	57	57
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	0	969	940	884
Calcium	ppm	ASTM D5185m		1131	1092	1210
Phosphorus	ppm	ASTM D5185m		1060	1089	952
Zinc	ppm	ASTM D5185m		1296	1210	1161
Sulfur	ppm	ASTM D5185m		3436	3052	3420
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.1	15.4	17.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	9.5	9.6	9.90
Visc @ 100°C	cSt	ASTM D445	14	13.1	13.1	13.4



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : RPL0017937

Lab Number : 06121992

Unique Number : 10936143

Test Package : FLEET

Received : 19 Mar 2024

Tested : 19 Mar 2024

Diagnosed : 21 Mar 2024 - Don Baldrige

RTL PACLEASE - 7006 - Pico Rivera

7837 Telegraph Rd

Pico Rivera, CA

US 90660

Contact: GERARDO CARROLA

carrolag@rushenterprises.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)