



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
731122
Component
Natural Gas Engine
Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0114026 | GFL0109772 | GFL0103356 |
| Sample Date | | Client Info | | 14 Mar 2024 | 09 Feb 2024 | 02 Jan 2024 |
| Machine Age | hrs | Client Info | | 4335 | 0 | 4022 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Filter Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >50 | 11 | 12 | 10 |
| Chromium | ppm | ASTM D5185m | >4 | 0 | 1 | 1 |
| Nickel | ppm | ASTM D5185m | >2 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Silver | ppm | ASTM D5185m | >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >9 | <1 | 6 | 2 |
| Lead | ppm | ASTM D5185m | >30 | <1 | 7 | 2 |
| Copper | ppm | ASTM D5185m | >35 | 11 | 12 | 2 |
| Tin | ppm | ASTM D5185m | >4 | 0 | 1 | 2 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION







There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >+100 | 3 | 17 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 5 | 0 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | | 0 | 0 | 0 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 10.4 | 11.8 | 9.5 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 19.6 | 25.6 | 19.4 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|-------------|------|------|
| Sodium | ppm | ASTM D5185m | | 3 | 1 | 7 |
| Boron | ppm | ASTM D5185m | 50 | 13 | 5 | 26 |
| Barium | ppm | ASTM D5185m | 5 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 50 | 51 | 59 | 58 |
| Manganese | ppm | ASTM D5185m | 0 | 0 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | 560 | 517 | 581 | 566 |
| Calcium | ppm | ASTM D5185m | 1510 | 1541 | 1461 | 1673 |
| Phosphorus | ppm | ASTM D5185m | 780 | 762 | 720 | 826 |
| Zinc | ppm | ASTM D5185m | 870 | 945 | 965 | 1026 |
| Sulfur | ppm | ASTM D5185m | 2040 | 2795 | 2261 | 2567 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 17.7 | 22.3 | 16.7 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 10.2 | 5.5 | 2.6 | 5.2 |
| Visc @ 100°C | cSt | ASTM D445 | 15.1 | 14.4 | 13.2 | 14.5 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0114026
Lab Number : 06122032
Unique Number : 10936183
Test Package : FLEET

Received : 19 Mar 2024
Tested : 19 Mar 2024
Diagnosed : 19 Mar 2024 - Wes Davis

GFL Environmental - 836 - Kansas City Hauling
 7801 East Truman Road
 Kansas City, MO
 US 64126
 Contact: Loyce Stewart
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: