



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[W65260-1]
 Machine Id
JOHN DEERE 310E 1DW310EXVMF710644
 Component
Hydraulic System
 Fluid
JOHN DEERE HYDRAU (50 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0206358	JR0198033	JR0170701
Sample Date		Client Info		14 Mar 2024	29 Jan 2024	15 Jul 2023
Machine Age	hrs	Client Info		3302	2640	2640
Oil Age	hrs	Client Info		0	568	568
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	N/A	Not Chngd
Filter Changed		Client Info		Not Chngd	N/A	Not Chngd
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>50	16	12	10
Iron	ppm	ASTM D5185m	>71	8	10	9
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>6	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>11	4	4	5
Lead	ppm	ASTM D5185m	>13	0	<1	<1
Copper	ppm	ASTM D5185m	>21	2	3	2
Tin	ppm	ASTM D5185m	>5	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicon	ppm	ASTM D5185m	>24	4	4	3
Potassium	ppm	ASTM D5185m	>20	0	2	3
Water		WC Method	>0.075	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>80000	20051	---	11580
Particles >6µm		ASTM D7647	>5000	987	---	2383
Particles >14µm		ASTM D7647	>640	40	---	214
Particles >21µm		ASTM D7647	>160	12	---	53
Particles >38µm		ASTM D7647	>40	1	---	2
Particles >71µm		ASTM D7647	>10	0	---	0
Oil Cleanliness		ISO 4406 (c)	>23/19/16	22/17/12	---	21/18/15
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	▲ MODER	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>21	<1	2	0
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	<1	0
Molybdenum	ppm	ASTM D5185m		0	0	2
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m		0	0	6
Calcium	ppm	ASTM D5185m	87	63	29	78
Phosphorus	ppm	ASTM D5185m	727	504	517	483
Zinc	ppm	ASTM D5185m	900	666	679	672
Sulfur	ppm	ASTM D5185m	1500	4202	3571	3898
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.62	0.54	0.62
Visc @ 40°C	cSt	ASTM D445	65	52.9	53.5	53.1



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0206358 **Received** : 19 Mar 2024
Lab Number : 06122270 **Tested** : 20 Mar 2024
Unique Number : 10936421 **Diagnosed** : 20 Mar 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

CARLTON'S BACKHOE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: LEO

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (704)547-0211

F: