



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Store 2 - Beaver
Machine Id
JOHN DEERE EL55

Component
Diesel Engine
Fluid
SHELL ROTELLA T 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0041894	LEC0040496	LEC0025430
Sample Date		Client Info		15 Mar 2024	07 Apr 2023	21 Jan 2022
Machine Age	hrs	Client Info		1567	1125	679
Oil Age	hrs	Client Info		442	446	679
Filter Age	hrs	Client Info		442	446	679
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	15	25	32
Chromium	ppm	ASTM D5185m	>11	0	0	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>31	3	3	5
Lead	ppm	ASTM D5185m	>26	0	0	1
Copper	ppm	ASTM D5185m	>26	3	14	66
Tin	ppm	ASTM D5185m	>4	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>120	9	11	▲ 37
Potassium	ppm	ASTM D5185m	>20	1	6	5
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.6	0.7
Nitration	Abs/cm	*ASTM D7624	>20	9.7	9.0	11.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.3	22.4	30.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	2	4	15
Boron	ppm	ASTM D5185m	316	183	137	145
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	1.2	197	35	213
Manganese	ppm	ASTM D5185m		0	<1	1
Magnesium	ppm	ASTM D5185m	24	653	118	635
Calcium	ppm	ASTM D5185m	2292	1617	2235	1604
Phosphorus	ppm	ASTM D5185m	1064	912	931	801
Zinc	ppm	ASTM D5185m	1160	1112	1280	1058
Sulfur	ppm	ASTM D5185m	4996	3516	3572	2798
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.3	19.9	27.7
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	7.7	5.7	7.7
Visc @ 100°C	cSt	ASTM D445	15.7	13.5	14.2	12.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0041894 **Received** : 20 Mar 2024
Lab Number : 06123325 **Tested** : 21 Mar 2024
Unique Number : 10937476 **Diagnosed** : 21 Mar 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

C. J. HUGHES CONSTRUCTION
 PO BOX 7305
 HUNTINGTON, WV
 US 25776
 Contact: DEWEY SHEPPARD
 dsheppard@cjhughes.com
 T: (304)522-3868
 F: (304)743-5449

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)