



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**Store 9 - Marietta**  
Machine Id  
**FREIGHTLINER 56**

Component  
**Diesel Engine**  
Fluid  
**SHELL ROTELLA T 15W40 (10 GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LEC0048375</b>	LEC0045458	LEC0045796
Sample Date		Client Info		<b>15 Mar 2024</b>	19 Jan 2024	02 Jan 2024
Machine Age	mls	Client Info		<b>627810</b>	619021	616564
Oil Age	mls	Client Info		<b>10000</b>	10000	10000
Filter Age	mls	Client Info		<b>10000</b>	10000	10000
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	ABNORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	<b>17</b>	11	28
Chromium	ppm	ASTM D5185m	>5	<b>&lt;1</b>	1	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>30	<b>2</b>	2	6
Lead	ppm	ASTM D5185m	>30	<b>14</b>	6	▲ 34
Copper	ppm	ASTM D5185m	>150	<b>0</b>	1	1
Tin	ppm	ASTM D5185m	>5	<b>0</b>	<1	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION







There is no indication of any contamination in the component.

Silicon	ppm	ASTM D5185m	>120	<b>7</b>	7	7
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	3	5
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>1.1</b>	0.5	1.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.1</b>	8.1	12.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>27.4</b>	24.8	29.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>2</b>	0	<1
Boron	ppm	ASTM D5185m	316	<b>216</b>	312	161
Barium	ppm	ASTM D5185m	0.0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	1.2	<b>141</b>	130	130
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	24	<b>757</b>	667	699
Calcium	ppm	ASTM D5185m	2292	<b>1826</b>	1399	1557
Phosphorus	ppm	ASTM D5185m	1064	<b>844</b>	741	746
Zinc	ppm	ASTM D5185m	1160	<b>1004</b>	845	890
Sulfur	ppm	ASTM D5185m	4996	<b>3201</b>	2565	2516
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>21.6</b>	18.1	24.4
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	<b>8.1</b>	8.9	7.0
Visc @ 100°C	cSt	ASTM D445	15.7	<b>14.0</b>	13.6	14.2



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : LEC0048375  
**Lab Number** : 06123342  
**Unique Number** : 10937493  
**Test Package** : CONST ( Additional Tests: TBN )

**Received** : 20 Mar 2024  
**Tested** : 21 Mar 2024  
**Diagnosed** : 22 Mar 2024 - Sean Felton

**HALL DRILLING LLC**  
 PO BOX 249  
 ELLENBORO, WV  
 US 26346

Contact: CHRIS PETROVICH  
 chrispetrovich@halldrilling.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (304)869-3404  
 F: (304)869-3408