



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	ABNORMAL
FLUID CONDITION	NORMAL

Area
Store 9 - Marietta
Machine Id
PETERBILT 1007

Component
Diesel Engine
Fluid
SHELL ROTELLA T 15W40 (10 GAL)

RECOMMENDATION

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0048374	LEC0045460	LEC0044832
Sample Date		Client Info		10 Mar 2024	22 Jan 2024	26 Nov 2023
Machine Age	hrs	Client Info		25091	24659	24131
Oil Age	hrs	Client Info		400	400	400
Filter Age	hrs	Client Info		400	400	400
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				ABNORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>110	24	28	20
Chromium	ppm	ASTM D5185m	>4	0	2	<1
Nickel	ppm	ASTM D5185m	>2	0	1	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	5	4
Lead	ppm	ASTM D5185m	>45	1	<1	4
Copper	ppm	ASTM D5185m	>85	0	1	<1
Tin	ppm	ASTM D5185m	>4	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.


Silicon	ppm	ASTM D5185m	>120	▲ 23	8	7
Potassium	ppm	ASTM D5185m	>20	<1	3	2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.4	1.6	1.2
Nitration	Abs/cm	*ASTM D7624	>20	8.7	10.4	8.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.7	25.8	24.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	0	1
Boron	ppm	ASTM D5185m	316	113	264	288
Barium	ppm	ASTM D5185m	0.0	0	0	0
Molybdenum	ppm	ASTM D5185m	1.2	60	131	135
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	24	176	659	705
Calcium	ppm	ASTM D5185m	2292	3164	1386	1644
Phosphorus	ppm	ASTM D5185m	1064	943	735	785
Zinc	ppm	ASTM D5185m	1160	1119	857	912
Sulfur	ppm	ASTM D5185m	4996	3881	2499	2601
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.1	17.8	16.8
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	9.8	9.3	9.9
Visc @ 100°C	cSt	ASTM D445	15.7	13.8	13.7	13.6


▲ Silicon (ppm)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0048374 **Received** : 20 Mar 2024
Lab Number : 06123344 **Tested** : 21 Mar 2024
Unique Number : 10937495 **Diagnosed** : 22 Mar 2024 - Sean Felton
Test Package : CONST (Additional Tests: TBN)

HALL DRILLING LLC
 PO BOX 249
 ELLENBORO, WV
 US 26346

Contact: CHRIS PETROVICH
 chrispetrovich@halldrilling.com
 T: (304)869-3404
 F: (304)869-3408

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)