



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
749005-310061

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0106812	GFL0106823	GFL0084580
Sample Date		Client Info		13 Mar 2024	21 Feb 2024	21 Dec 2023
Machine Age	hrs	Client Info		14622	14444	14082
Oil Age	hrs	Client Info		600	0	625869
Filter Age	hrs	Client Info		600	0	625869
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	6	8	20
Chromium	ppm	ASTM D5185m	>20	0	<1	1
Nickel	ppm	ASTM D5185m	>4	0	0	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	<1	3
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	0	<1	2
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	4	5	18
Potassium	ppm	ASTM D5185m	>20	<1	7	29
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	0.0
Soot %	%	*ASTM D7844	>3	0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	8.0	9.5	9.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.3	19.7	19.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		10	63	115
Boron	ppm	ASTM D5185m	0	27	20	11
Barium	ppm	ASTM D5185m	0	0	0	13
Molybdenum	ppm	ASTM D5185m	60	49	52	58
Manganese	ppm	ASTM D5185m	0	0	<1	2
Magnesium	ppm	ASTM D5185m	1010	602	497	555
Calcium	ppm	ASTM D5185m	1070	1718	1490	1454
Phosphorus	ppm	ASTM D5185m	1150	865	676	773
Zinc	ppm	ASTM D5185m	1270	1052	760	908
Sulfur	ppm	ASTM D5185m	2060	3108	2222	2457
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.4	16.8	17.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.4	6.3	6.7
Visc @ 100°C	cSt	ASTM D445	15.4	14.6	14.6	14.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0106812
Lab Number : 06123379
Unique Number : 10937530
Test Package : FLEET
Received : 20 Mar 2024
Tested : 21 Mar 2024
Diagnosed : 22 Mar 2024 - Don Baldrige

GFL Environmental - 856 - Houston South
 8515 Highway 6 South
 Houston, TX
 US 77083
 Contact: Apolinar Zacarias
 pzacariascano@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: