



McCLUNG-LOGAN
EQUIPMENT COMPANY, INC.

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[W05004118]
Machine Id
VOLVO A40G 341427
Component
Diesel Engine
Fluid
MOBIL 15W40 (15 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W05004118)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		ML0000396	VCP189544	VCP420840
Sample Date		Client Info		19 Mar 2024	08 Jan 2024	27 Oct 2023
Machine Age	hrs	Client Info		11295	11033	10775
Oil Age	hrs	Client Info		250	250	250
Filter Age	hrs	Client Info		250	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	2	1	3
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>2	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	3	2	2
Lead	ppm	ASTM D5185m	>40	0	<1	0
Copper	ppm	ASTM D5185m	>330	<1	0	<1
Tin	ppm	ASTM D5185m	>15	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	4	5	4
Potassium	ppm	ASTM D5185m	>20	2	<1	5
Fuel		WC Method	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.3	7.6	5.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.4	23.3	22.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>118	4	<1	5
Boron	ppm	ASTM D5185m		323	300	363
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		122	113	120
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		668	626	598
Calcium	ppm	ASTM D5185m		1495	1579	1500
Phosphorus	ppm	ASTM D5185m		737	735	697
Zinc	ppm	ASTM D5185m		852	933	855
Sulfur	ppm	ASTM D5185m		2916	2537	3517
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.0	17.5	16.1
Base Number (BN)	mg KOH/g	ASTM D2896		8.6	8.6	9.0
Visc @ 100°C	cSt	ASTM D445		12.8	13.0	12.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : ML0000396
Lab Number : 06124197
Unique Number : 10938348
Test Package : CONST (Additional Tests: TBN)

MCCLUNG-LOGAN EQUIPMENT CO - MANASSAS
 8450 QUARRY ROAD
 MANASSAS, VA
 US 20110
 Contact: MIKE MAYHUGH
 MMAYHUGH@MCCLUNG-LOGAN.COM
 T: (703)393-7344
 F: (703)393-7844

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)