



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
FREIGHTLINER 2-218

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 15W40 (52 QTS)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0871764	WC0740649	WC0324519
Sample Date		Client Info		05 Mar 2024	15 Aug 2023	30 Mar 2023
Machine Age	hrs	Client Info		25362	24286	23407
Oil Age	hrs	Client Info		1076	879	669
Filter Age	hrs	Client Info		1076	879	669
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>200	24	38	42
Chromium	ppm	ASTM D5185m	>20	2	4	2
Nickel	ppm	ASTM D5185m	>2	0	2	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	<1	1	<1
Aluminum	ppm	ASTM D5185m	>30	30	28	17
Lead	ppm	ASTM D5185m	>30	0	0	0
Copper	ppm	ASTM D5185m	>30	4	7	10
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	5	10	7
Potassium	ppm	ASTM D5185m	>20	52	50	18
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	1.2	0.5
Nitration	Abs/cm	*ASTM D7624	>20	10.5	11.7	11.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.7	25.7	24.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	3	3	3
Boron	ppm	ASTM D5185m	250	40	33	40
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	14	4	6
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m	450	763	766	819
Calcium	ppm	ASTM D5185m	3000	1370	1449	1492
Phosphorus	ppm	ASTM D5185m	1150	737	742	782
Zinc	ppm	ASTM D5185m	1350	844	875	930
Sulfur	ppm	ASTM D5185m	4250	3362	2810	3668
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.1	21.6	22.8
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	5.6	6.0	4.4
Visc @ 100°C	cSt	ASTM D445	14.4	14.1	15.1	14.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WC0871764

Lab Number : 06124227

Unique Number : 10938378

Test Package : FLEET

Received : 20 Mar 2024

Tested : 21 Mar 2024

Diagnosed : 21 Mar 2024 - Wes Davis

ALASKA WEST EXPRESS

1095 SANDURI STREET

FAIRBANKS, AK

US 99701

Contact: TOM DOUTHIT

tdouthit@lynden.com

T: (907)452-4355

F: (907)328-1956

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)