



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 245G 1FF245GXCLF801779

Component
Pump Drive

Fluid
{not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0204127	JR0171186	JR0151414
Sample Date		Client Info		19 Mar 2024	13 Jun 2023	21 Nov 2022
Machine Age	hrs	Client Info		2473	1955	1493
Oil Age	hrs	Client Info		518	1955	500
Filter Age	hrs	Client Info		0	0	500
Oil Changed		Client Info		Not Changd	Changed	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		16	21	8
Iron	ppm	ASTM D5185m	>151	89	80	68
Chromium	ppm	ASTM D5185m	>11	1	2	1
Nickel	ppm	ASTM D5185m	>10	0	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		<1	0	<1
Aluminum	ppm	ASTM D5185m	>21	4	5	2
Lead	ppm	ASTM D5185m	>51	<1	0	<1
Copper	ppm	ASTM D5185m	>51	1	<1	3
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	MODER	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Silicon	ppm	ASTM D5185m	>31	9	10	8
Potassium	ppm	ASTM D5185m	>20	4	1	0
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sodium	ppm	ASTM D5185m	>51	0	2	2
Boron	ppm	ASTM D5185m		216	237	227
Barium	ppm	ASTM D5185m		5	1	0
Molybdenum	ppm	ASTM D5185m		208	196	204
Manganese	ppm	ASTM D5185m		1	2	1
Magnesium	ppm	ASTM D5185m		511	548	542
Calcium	ppm	ASTM D5185m		2421	2356	2332
Phosphorus	ppm	ASTM D5185m		986	1044	1010
Zinc	ppm	ASTM D5185m		1167	1209	1161
Sulfur	ppm	ASTM D5185m		5278	6382	5659
Visc @ 40°C	cSt	ASTM D445		71.7	73.8	76.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0204127 **Received** : 21 Mar 2024
Lab Number : 06125159 **Tested** : 24 Mar 2024
Unique Number : 10939310 **Diagnosed** : 24 Mar 2024 - Wes Davis
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269

Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (704)597-0211
 F: (704)596-6198