



# LIEBHERR

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**LIEBHERR LH50M 1216-117615**  
Component  
**Front Differential**  
Fluid  
**LIEBHERR GEAR BASIC 90 LS (--- GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LH0268640</b>	LH06073287	LH0244103
Sample Date		Client Info		<b>05 Mar 2024</b>	28 Jan 2024	14 Apr 2023
Machine Age	hrs	Client Info		<b>5510</b>	1216	6895
Oil Age	hrs	Client Info		<b>510</b>	0	1000
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changed</b>	N/A	Changed
Filter Changed		Client Info		<b>Not Changed</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>190	<b>0</b>	3	2
Chromium	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>5	<b>0</b>	<1	0
Lead	ppm	ASTM D5185m	>15	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>70	<b>0</b>	0	<1
Tin	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	<b>0</b>	<1	0
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	2	<1
Water		WC Method	>.2	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	1	<1
Boron	ppm	ASTM D5185m	0	<b>0</b>	0	1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>0</b>	0	0
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m	<1	<b>0</b>	1	<1
Calcium	ppm	ASTM D5185m	<1	<b>4</b>	10	31
Phosphorus	ppm	ASTM D5185m	2143	<b>2252</b>	2327	2248
Zinc	ppm	ASTM D5185m	<1	<b>&lt;1</b>	2	11
Sulfur	ppm	ASTM D5185m	23468	<b>30386</b>	28565	31777
Visc @ 40°C	cSt	ASTM D445	170	<b>181</b>	192	189



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : LH0268640  
**Lab Number** : 06125230  
**Unique Number** : 10939381  
**Test Package** : CONST  
**Received** : 21 Mar 2024  
**Tested** : 24 Mar 2024  
**Diagnosed** : 24 Mar 2024 - Wes Davis

**RECO EQUIPMENT INC**  
 10461 GRAND RIVER RD  
 BRIGHTON, MI  
 US 48116  
 Contact: MATT VISEL  
 MVISEL@RECOEQUIP.COM  
 T: (810)299-1731  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)