



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**LINKBELT 360X2RT C-3 (S/N 350Q5NCMHR1270)**

Component  
**Front Left Planetary**

Fluid  
**PHILLIPS EP5 80W90 SAE (1 GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0899786</b>	WC0849472	WC0819369
Sample Date		Client Info		<b>18 Mar 2024</b>	19 Sep 2023	27 May 2023
Machine Age	hrs	Client Info		<b>14075</b>	13074	12786
Oil Age	hrs	Client Info		<b>1001</b>	624	12786
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Changed</b>	N/A	Changed
Filter Changed		Client Info		<b>Not Changed</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	<b>28</b>	12	17
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	0	<1
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>0</b>	0	<1
Lead	ppm	ASTM D5185m	>25	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>75	<b>&lt;1</b>	2	2
Tin	ppm	ASTM D5185m	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>MODER</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<b>4</b>	<1	2
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	1	2
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>1</b>	0	2
Boron	ppm	ASTM D5185m		<b>37</b>	46	58
Barium	ppm	ASTM D5185m		<b>1</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>0</b>	1	<1
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m		<b>0</b>	1	0
Calcium	ppm	ASTM D5185m		<b>13</b>	10	12
Phosphorus	ppm	ASTM D5185m		<b>493</b>	415	452
Zinc	ppm	ASTM D5185m		<b>13</b>	4	0
Sulfur	ppm	ASTM D5185m		<b>21457</b>	16786	20926
Visc @ 40°C	cSt	ASTM D445		<b>124</b>	115	125



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0899786  
**Lab Number** : 06125238  
**Unique Number** : 10939389  
**Test Package** : CONST

**Received** : 21 Mar 2024  
**Tested** : 24 Mar 2024  
**Diagnosed** : 24 Mar 2024 - Wes Davis

**FRANKLIN IRON & METAL CORP**  
 1939 EAST 1ST ST  
 DAYTON, OH  
 US 45403  
 Contact: BILL PITTL JR  
 parts@frankliniron.com  
 T: (937)253-8184  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)