WEAR CONTAMINATION FLUID CONDITION


NORMAL NORMAL NORMAL



Ascendum Machinery VOLVO EC300E 300E316668

Component Radiator Coolant

VOLVO VCS-2 Coolant (Orang	e) (GAL)						
RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
No corrective action is recommended at this time. The fluid is suitable for further service.	Sample Number		Client Info		ASC0000848		
	Sample Date		Client Info		18 Mar 2024		
	Machine Age	hrs	Client Info		1969		
	Oil Age	hrs	Client Info		1969		
	Filter Age	hrs	Client Info		0		
	Oil Changed		Client Info		Not Changd		
	Filter Changed		Client Info		N/A		
	Sample Status				NORMAL		
WEAR	Total Dissolved Solids				259.5		
	Coolant Appearance		*Visual	Clear	normal		
CONTAMINATION	Water		WC Method		NEG		
FLUID CONDITION nation in the coolant.	Boiling Point	°C	WC Method		225		
Carboxylate test failed. Glycol and nitrite levels are acceptable. The pH level of this fluid is within the acceptable limits.	Specific Gravity		*ASTM D1298		1.065		
	рН	Scale 0-14	ASTM D1287		7.53		
	Nitrites	ppm	AP-053:2009		560		
	Reserve Alkalinity	Scale 0-20	*ASTM D1121				
	Percentage Glycol	%	ASTM D3321		48.6		
	Freezing Point	°F	ASTM D3321		-31		
	Carboxylate				fail		
	Coolant Color		*Visual		Yllow		







Laboratory

Sample No.

Unique Number : 10939484

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : ASC0000848 Lab Number : 06125333

Received : 21 Mar 2024 **Tested** : 26 Mar 2024 Diagnosed : 26 Mar 2024 - Jonathan Hester

Test Package : COOL- (Additional Tests: BoilingPoint, COOL, GlycolType) To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

рΗ

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Nitrites

3000 2800

2400

2000 1800

1400

1000 800

> 400 200

> > MIDSOUTH LAND SERVICES

138 HILLCREST DR ADVANCE, NC US 27006

Contact: Service Manager

T:

F: