



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |



Machine Id  
**525056-651122**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>GFL0114451</b>  | GFL0114484  | GFL0100539  |
| Sample Date    |     | Client Info |           | <b>11 Mar 2024</b> | 05 Mar 2024 | 20 Nov 2023 |
| Machine Age    | mls | Client Info |           | <b>705936</b>      | 750842      | 34374       |
| Oil Age        | mls | Client Info |           | <b>750842</b>      | 0           | 34374       |
| Filter Age     | mls | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Changed    |     | Client Info |           | <b>Not Changd</b>  | Changed     | Not Changd  |
| Filter Changed |     | Client Info |           | <b>Not Changd</b>  | Changed     | Not Changd  |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >75  | <b>5</b>     | 21   | 16   |
| Chromium     | ppm    | ASTM D5185m | >4   | <b>&lt;1</b> | <1   | 1    |
| Nickel       | ppm    | ASTM D5185m | >7   | <b>&lt;1</b> | 0    | 0    |
| Titanium     | ppm    | ASTM D5185m | >2   | <b>&lt;1</b> | 0    | 0    |
| Silver       | ppm    | ASTM D5185m | >2   | <b>0</b>     | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >30  | <b>3</b>     | 1    | 1    |
| Lead         | ppm    | ASTM D5185m | >40  | <b>&lt;1</b> | 2    | <1   |
| Copper       | ppm    | ASTM D5185m | >200 | <b>&lt;1</b> | 3    | 1    |
| Tin          | ppm    | ASTM D5185m | >4   | <b>&lt;1</b> | 0    | <1   |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | 0    | <1   |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

**CONTAMINATION**







There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >25   | <b>4</b>       | 3     | 4     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>3</b>       | 0     | <1    |
| Fuel             |          | WC Method   | >3.0  | <b>&lt;1.0</b> | <1.0  | <1.0  |
| Water            |          | WC Method   | >0.2  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >4    | <b>0.3</b>     | 2     | 0.9   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>4.7</b>     | 9.4   | 6.7   |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>17.7</b>    | 22.1  | 19.4  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.2  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |              |      |      |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium           | ppm      | ASTM D5185m |      | <b>3</b>     | 14   | 8    |
| Boron            | ppm      | ASTM D5185m | 0    | <b>3</b>     | 3    | 2    |
| Barium           | ppm      | ASTM D5185m | 0    | <b>2</b>     | 0    | 0    |
| Molybdenum       | ppm      | ASTM D5185m | 60   | <b>91</b>    | 61   | 59   |
| Manganese        | ppm      | ASTM D5185m | 0    | <b>&lt;1</b> | 0    | 0    |
| Magnesium        | ppm      | ASTM D5185m | 1010 | <b>1468</b>  | 1018 | 961  |
| Calcium          | ppm      | ASTM D5185m | 1070 | <b>1642</b>  | 1176 | 1107 |
| Phosphorus       | ppm      | ASTM D5185m | 1150 | <b>1424</b>  | 1107 | 1057 |
| Zinc             | ppm      | ASTM D5185m | 1270 | <b>1891</b>  | 1309 | 1238 |
| Sulfur           | ppm      | ASTM D5185m | 2060 | <b>5315</b>  | 3615 | 3083 |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>13.3</b>  | 16.0 | 14.1 |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 9.8  | <b>9.2</b>   | 8.4  | 8.7  |
| Visc @ 100°C     | cSt      | ASTM D445   | 15.4 | <b>14.5</b>  | 13.6 | 13.5 |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0114451  
**Lab Number** : 06125401  
**Unique Number** : 10939552  
**Test Package** : FLEET

**Received** : 21 Mar 2024  
**Tested** : 22 Mar 2024  
**Diagnosed** : 25 Mar 2024 - Don Baldrige

**GFL Environmental - 865 - East Mount Hauling**  
 7213 East Mount Houston Road  
 Houston, TX  
 US 77050  
 Contact: Saul Castillo  
 saul.castillo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: