



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
914049
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0084805	GFL0084802	GFL0084769
Sample Date		Client Info		11 Mar 2024	08 Feb 2024	27 Dec 2023
Machine Age	hrs	Client Info		967	967	630
Oil Age	hrs	Client Info		967	630	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Filter Changed		Client Info		Changed	N/A	N/A
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>120	27	14	43
Chromium	ppm	ASTM D5185m	>20	1	<1	<1
Nickel	ppm	ASTM D5185m	>5	4	1	4
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	<1	0	1
Aluminum	ppm	ASTM D5185m	>20	4	1	6
Lead	ppm	ASTM D5185m	>40	<1	0	<1
Copper	ppm	ASTM D5185m	>330	166	25	171
Tin	ppm	ASTM D5185m	>15	1	0	3
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	12	8	50
Potassium	ppm	ASTM D5185m	>20	8	5	12
Fuel		WC Method	>3.0	<1.0	<1.0	0.5
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>4	0.3	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	8.5	7.5	10.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.2	19.4	23.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		5	0	4
Boron	ppm	ASTM D5185m	0	11	15	159
Barium	ppm	ASTM D5185m	0	0	8	0
Molybdenum	ppm	ASTM D5185m	60	92	65	108
Manganese	ppm	ASTM D5185m	0	1	0	4
Magnesium	ppm	ASTM D5185m	1010	1398	880	723
Calcium	ppm	ASTM D5185m	1070	1574	989	1301
Phosphorus	ppm	ASTM D5185m	1150	1512	844	737
Zinc	ppm	ASTM D5185m	1270	1823	1127	872
Sulfur	ppm	ASTM D5185m	2060	4309	2672	2261
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.6	15.5	21.8
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.2	8.0	7.4
Visc @ 100°C	cSt	ASTM D445	15.4	13.4	13.5	10.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0084805 **Received** : 21 Mar 2024
Lab Number : 06125506 **Tested** : 22 Mar 2024
Unique Number : 10939657 **Diagnosed** : 25 Mar 2024 - Don Baldrige
Test Package : FLEET

GFL Environmental - 959A - Urbana HC
 4808 cunningham Rd
 Urbana, IL
 US 61802
 Contact: Kristine Tryon
 Ktryon@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: