



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |

Machine Id  
**JOHN DEERE 844K 1DW844KXKGF674415**

Component  
**Transmission (Manual)**

Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (--- QTS)**

### RECOMMENDATION

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>JR0199965</b>   | JR0148784   | JR0148519   |
| Sample Date    |     | Client Info |           | <b>18 Mar 2024</b> | 27 Mar 2023 | 13 Dec 2022 |
| Machine Age    | hrs | Client Info |           | <b>17940</b>       | 15963       | 15000       |
| Oil Age        | hrs | Client Info |           | <b>0</b>           | 0           | 0           |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Changed    |     | Client Info |           | <b>Changed</b>     | Changed     | Not Changd  |
| Filter Changed |     | Client Info |           | <b>Changed</b>     | Changed     | Not Changd  |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

### WEAR

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| PQ           |        | ASTM D8184  | >95  | <b>19</b>    | 15   | 12   |
| Iron         | ppm    | ASTM D5185m | >200 | <b>35</b>    | 31   | 24   |
| Chromium     | ppm    | ASTM D5185m | >5   | <b>0</b>     | 0    | <1   |
| Nickel       | ppm    | ASTM D5185m | >5   | <b>0</b>     | 0    | 0    |
| Titanium     | ppm    | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| Silver       | ppm    | ASTM D5185m | >7   | <b>0</b>     | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >25  | <b>&lt;1</b> | <1   | <1   |
| Lead         | ppm    | ASTM D5185m | >45  | <b>0</b>     | 0    | 0    |
| Copper       | ppm    | ASTM D5185m | >225 | <b>4</b>     | 3    | 4    |
| Tin          | ppm    | ASTM D5185m | >10  | <b>0</b>     | 0    | <1   |
| Vanadium     | ppm    | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

### CONTAMINATION







There is no indication of any contamination in the fluid.

|                  |        |             |       |              |       |       |
|------------------|--------|-------------|-------|--------------|-------|-------|
| Silicon          | ppm    | ASTM D5185m | >125  | <b>3</b>     | 6     | 4     |
| Potassium        | ppm    | ASTM D5185m | >20   | <b>0</b>     | 0     | 0     |
| Water            |        | WC Method   | >0.1  | <b>NEG</b>   | NEG   | NEG   |
| Silt             | scalar | *Visual     | NONE  | <b>NONE</b>  | NONE  | NONE  |
| Debris           | scalar | *Visual     | NONE  | <b>NONE</b>  | NONE  | NONE  |
| Sand/Dirt        | scalar | *Visual     | NONE  | <b>NONE</b>  | NONE  | NONE  |
| Appearance       | scalar | *Visual     | NORML | <b>NORML</b> | NORML | NORML |
| Odor             | scalar | *Visual     | NORML | <b>NORML</b> | NORML | NORML |
| Emulsified Water | scalar | *Visual     | >0.1  | <b>NEG</b>   | NEG   | NEG   |

### FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

|             |     |             |      |              |      |      |
|-------------|-----|-------------|------|--------------|------|------|
| Sodium      | ppm | ASTM D5185m |      | <b>2</b>     | 0    | <1   |
| Boron       | ppm | ASTM D5185m | 6    | <b>2</b>     | 0    | <1   |
| Barium      | ppm | ASTM D5185m | 0    | <b>0</b>     | 0    | 0    |
| Molybdenum  | ppm | ASTM D5185m | 0    | <b>4</b>     | 0    | <1   |
| Manganese   | ppm | ASTM D5185m |      | <b>&lt;1</b> | <1   | <1   |
| Magnesium   | ppm | ASTM D5185m | 145  | <b>97</b>    | 97   | 90   |
| Calcium     | ppm | ASTM D5185m | 3570 | <b>3262</b>  | 3737 | 3278 |
| Phosphorus  | ppm | ASTM D5185m | 1290 | <b>1021</b>  | 1058 | 927  |
| Zinc        | ppm | ASTM D5185m | 1640 | <b>1108</b>  | 1242 | 1110 |
| Sulfur      | ppm | ASTM D5185m |      | <b>3807</b>  | 3946 | 3490 |
| Visc @ 40°C | cSt | ASTM D445   | 57.0 | <b>50.8</b>  | 50.8 | 50.9 |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : JR0199965 **Received** : 21 Mar 2024  
**Lab Number** : 06125832 **Tested** : 25 Mar 2024  
**Unique Number** : 10939983 **Diagnosed** : 25 Mar 2024 - Wes Davis  
**Test Package** : CONST ( Additional Tests: PQ )

**JRE - ASHLAND**  
 11047 LEADBETTER RD  
 ASHLAND, VA  
 US 23005  
 Contact: DAVID ZIEG  
 dzieg@jamesriverequipment.com  
 T: (804)798-6001  
 F: (804)798-0292

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)