



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
PETERBILT 846-5139
 Component
1 Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (48 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0019388	RPL0017420	RPL0015549
Sample Date		Client Info		28 Mar 2024	28 Dec 2023	27 Sep 2023
Machine Age	mls	Client Info		28779	22304	0
Oil Age	mls	Client Info		28779	22304	0
Filter Age	mls	Client Info		28779	22304	44
Oil Changed		Client Info		Not Changd	Not Changd	N/A
Filter Changed		Client Info		Not Changd	Not Changd	N/A
Sample Status				NORMAL	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>110	62	54	37
Chromium	ppm	ASTM D5185m	>4	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m	>2	<1	1	1
Aluminum	ppm	ASTM D5185m	>25	13	12	0
Lead	ppm	ASTM D5185m	>45	<1	<1	<1
Copper	ppm	ASTM D5185m	>85	13	13	13
Tin	ppm	ASTM D5185m	>4	2	2	1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION









There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	17	19	18
Potassium	ppm	ASTM D5185m	>20	40	33	32
Fuel	%	ASTM D3524	>5	<1.0	<1.0	0.7
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.3	0.2	0.1
Nitration	Abs/cm	*ASTM D7624	>20	11.3	10.9	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.6	25.5	22.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	1	<1
Boron	ppm	ASTM D5185m	0	9	13	25
Barium	ppm	ASTM D5185m	0	1	0	3
Molybdenum	ppm	ASTM D5185m	0	18	7	8
Manganese	ppm	ASTM D5185m		2	2	2
Magnesium	ppm	ASTM D5185m	0	876	828	686
Calcium	ppm	ASTM D5185m		1388	1297	1226
Phosphorus	ppm	ASTM D5185m		870	773	682
Zinc	ppm	ASTM D5185m		1011	922	803
Sulfur	ppm	ASTM D5185m		3556	2961	2772
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.3	21.5	18.0
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	4.8	4.3	5.2
Visc @ 100°C	cSt	ASTM D445	14	12.3	12.0	11.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0019388 **Received** : 11 Apr 2024
Lab Number : 06145599 **Tested** : 12 Apr 2024
Unique Number : 10970407 **Diagnosed** : 12 Apr 2024 - Jonathan Hester
Test Package : FLEET (Additional Tests: FuelDilution)

RTL PACLEASE - 7006 - Pico Rivera
 7837 Telegraph Rd
 Pico Rivera, CA
 US 90660
 Contact: GERARDO CARROLA
 carrolag@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: