



# VOLVO

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area

**[687011]**

Machine Id

**VOLVO EC200EL 314968**

Component

**Hydraulic System**

Fluid

**VOLVO SUPER HYDRAULIC OIL 46 (--- GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>VCP440915</b>	---	---
Sample Date		Client Info		<b>07 Mar 2024</b>	---	---
Machine Age	hrs	Client Info		<b>554</b>	---	---
Oil Age	hrs	Client Info		<b>554</b>	---	---
Filter Age	hrs	Client Info		<b>0</b>	---	---
Oil Changed		Client Info		<b>Not Chngd</b>	---	---
Filter Changed		Client Info		<b>Changed</b>	---	---
Sample Status				<b>NORMAL</b>	---	---

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>25	<b>0</b>	---	---
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	---	---
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	---	---
Titanium	ppm	ASTM D5185m		<b>0</b>	---	---
Silver	ppm	ASTM D5185m		<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>20	<b>0</b>	---	---
Lead	ppm	ASTM D5185m	>20	<b>0</b>	---	---
Copper	ppm	ASTM D5185m	>150	<b>7</b>	---	---
Tin	ppm	ASTM D5185m	>10	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---

### CONTAMINATION










The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicon	ppm	ASTM D5185m	>50	<b>2</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	---	---
Water		WC Method	>0.1	<b>NEG</b>	---	---
Particles >4µm		ASTM D7647	>40000	<b>3482</b>	---	---
Particles >6µm		ASTM D7647	>10000	<b>1042</b>	---	---
Particles >14µm		ASTM D7647	>2500	<b>100</b>	---	---
Particles >21µm		ASTM D7647	>640	<b>31</b>	---	---
Particles >38µm		ASTM D7647	>160	<b>1</b>	---	---
Particles >71µm		ASTM D7647	>40	<b>0</b>	---	---
Oil Cleanliness		ISO 4406 (c)	>22/20/18	<b>19/17/14</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	---	---

### FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	---	---
Boron	ppm	ASTM D5185m	14	<b>0</b>	---	---
Barium	ppm	ASTM D5185m	0.0	<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185m	0.0	<b>0</b>	---	---
Manganese	ppm	ASTM D5185m	0.0	<b>0</b>	---	---
Magnesium	ppm	ASTM D5185m	2.6	<b>&lt;1</b>	---	---
Calcium	ppm	ASTM D5185m	49	<b>80</b>	---	---
Phosphorus	ppm	ASTM D5185m	354	<b>365</b>	---	---
Zinc	ppm	ASTM D5185m	419	<b>463</b>	---	---
Sulfur	ppm	ASTM D5185m	3719	<b>1043</b>	---	---
Acid Number (AN)	mg KOH/g	ASTM D8045		<b>0.50</b>	---	---
Visc @ 40°C	cSt	ASTM D445	46	<b>42.8</b>	---	---



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : VCP440915  
**Lab Number** : 06145804  
**Unique Number** : 10975882  
**Test Package** : MOB 2

**RIPA AND ASSOCIATES**  
 10149 FISHER AVENUE  
 TAMPA, FL  
 US 33619  
 Contact: ROBERT TURNER  
 rturner@ripatampa.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)