



# WEAR CHECK

## OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id  
**3177**  
Component  
**Diesel Engine**  
Fluid  
**DIESEL ENGINE OIL 10W40 (--- QTS)**

### RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0906897</b>	WC0816682	WC0663071
Sample Date		Client Info		<b>06 Apr 2024</b>	06 Jul 2023	20 Apr 2023
Machine Age	mls	Client Info		<b>90145</b>	72585	65118
Oil Age	mls	Client Info		<b>46642</b>	25943	18476
Filter Age	mls	Client Info		<b>43503</b>	25943	18476
Oil Changed		Client Info		<b>Changed</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>Changed</b>	Not Changd	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>49</b>	28	17
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	0
Nickel	ppm	ASTM D5185m	>4	<b>2</b>	3	2
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>16</b>	13	9
Lead	ppm	ASTM D5185m	>40	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>330	<b>19</b>	14	14
Tin	ppm	ASTM D5185m	>15	<b>1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>14</b>	11	8
Potassium	ppm	ASTM D5185m	>20	<b>33</b>	31	29
Fuel	%	ASTM D3524	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>1</b>	0.7	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>12.1</b>	11.3	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>27.4</b>	24.8	20.0
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>5</b>	4	4
Boron	ppm	ASTM D5185m	250	<b>18</b>	27	30
Barium	ppm	ASTM D5185m	10	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	100	<b>33</b>	37	29
Manganese	ppm	ASTM D5185m		<b>2</b>	1	<1
Magnesium	ppm	ASTM D5185m	450	<b>825</b>	872	742
Calcium	ppm	ASTM D5185m	3000	<b>1481</b>	1527	1352
Phosphorus	ppm	ASTM D5185m	1150	<b>803</b>	812	673
Zinc	ppm	ASTM D5185m	1350	<b>926</b>	965	853
Sulfur	ppm	ASTM D5185m	4250	<b>3482</b>	3853	3121
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>22.9</b>	19.8	16.0
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>4.3</b>	5.7	4.9
Visc @ 100°C	cSt	ASTM D445	14.4	<b>12.3</b>	12.2	12.0


**FT-IR (Direct Trend)**




**Ferrous Alloys**




**Base Number**




**Non-ferrous Metals**




**Viscosity @ 100°C**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0906897  
**Lab Number** : 06146499  
**Unique Number** : 10976577  
**Test Package** : FLEET ( Additional Tests: FuelDilution )

**LTI/MILKY WAY - SUNNYSIDE**  
 333 MIDVALE RD  
 SUNNYSIDE, WA  
 US 98944  
 Contact: JERRY CRISP  
 jcrisp@ltii.lynden.com  
 T: (509)839-5844  
 F: (509)839-6556

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)