



WEAR **NORMAL**

CONTAMINATION **NORMAL**

FLUID CONDITION **NORMAL**

OIL ANALYSIS REPORT



Machine Id
FREIGHTLINER 9571888
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (17 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0015901	RPL0012541	RPL0009514
Sample Date		Client Info		02 Apr 2024	09 Jan 2024	10 Apr 2023
Machine Age	mls	Client Info		103529	98426	3692
Oil Age	mls	Client Info		5103	5501	3692
Filter Age	mls	Client Info		5103	5501	3692
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	MARGINAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	9	6	8
Chromium	ppm	ASTM D5185m	>5	<1	0	<1
Nickel	ppm	ASTM D5185m	>2	<1	0	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>30	5	5	4
Lead	ppm	ASTM D5185m	>30	1	0	<1
Copper	ppm	ASTM D5185m	>150	1	<1	0
Tin	ppm	ASTM D5185m	>5	1	0	1
Vanadium	ppm	ASTM D5185m		<1	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>20	6	4	5
Potassium	ppm	ASTM D5185m	>20	8	5	12
Fuel		WC Method	>5	<1.0	▲ 2.2	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	8.5	9.6	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.7	18.4	22.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	2	2
Boron	ppm	ASTM D5185m	0	69	84	32
Barium	ppm	ASTM D5185m	0	<1	0	0
Molybdenum	ppm	ASTM D5185m	0	81	119	56
Manganese	ppm	ASTM D5185m		1	0	<1
Magnesium	ppm	ASTM D5185m	0	547	679	653
Calcium	ppm	ASTM D5185m		1418	1246	1430
Phosphorus	ppm	ASTM D5185m		788	660	830
Zinc	ppm	ASTM D5185m		863	803	1018
Sulfur	ppm	ASTM D5185m		2695	2836	3222
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.1	16.6	20.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	8.2	6.0	8.9
Visc @ 100°C	cSt	ASTM D445	14	11.9	12.0	12.8


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0015901 **Received** : 12 Apr 2024
Lab Number : 06146867 **Tested** : 15 Apr 2024
Unique Number : 10976945 **Diagnosed** : 15 Apr 2024 - Wes Davis
Test Package : FLEET

RTL PACLEASE - 7004 - Austin
 1205 Smith Road
 Austin, TX
 US 78721
 Contact: David Johnson
 JohnsonD@RushEnterprises.com
 T: (512)401-7063
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)