



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area

**ELIZABETH R CHASE**

Machine Id

**[ELIZABETH R CHASE] 004 663777-4**

Component

**Port Reduction Gear**

Fluid

**CHEVRON MEROPA 320 (250 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0065670</b>	MW0065674	MW0066073
Sample Date		Client Info		<b>01 Apr 2024</b>	01 Mar 2024	01 Feb 2024
Machine Age	hrs	Client Info		<b>44944</b>	42232	43517
Oil Age	hrs	Client Info		<b>6389</b>	5677	5021
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>None</b>	None	None
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>97</b>	91	84
Chromium	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	2	1
Lead	ppm	ASTM D5185m	>100	<b>1</b>	0	0
Copper	ppm	ASTM D5185m	>50	<b>10</b>	1	1
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>3</b>	3	3
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	<1	0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>5</b>	5	4
Boron	ppm	ASTM D5185m	20	<b>18</b>	8	14
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>4</b>	0	1
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m		<b>21</b>	2	0
Calcium	ppm	ASTM D5185m	25	<b>65</b>	84	46
Phosphorus	ppm	ASTM D5185m	235	<b>345</b>	336	293
Zinc	ppm	ASTM D5185m		<b>48</b>	19	18
Sulfur	ppm	ASTM D5185m		<b>7350</b>	7574	5807
Acid Number (AN)	mg KOH/g	ASTM D8045	0.56	<b>0.56</b>	0.61	0.48
Visc @ 40°C	cSt	ASTM D445	304	<b>321</b>	320	320



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0065670

**Lab Number** : 06147507

**Unique Number** : 10977585

**Test Package** : MAR 2

**Received** : 12 Apr 2024

**Tested** : 15 Apr 2024

**Diagnosed** : 16 Apr 2024 - Don Baldrige

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: GLENN ELLIS

glen.ellis@ingrambarga.com

T: (270)415-4467

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)