



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
CHEMINEER A-804.3
 Component
Gearbox
 Fluid
JAX MAGNA-PLATE 220 FG (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

WEAR

All component wear rates are normal.











CONTAMINATION

There is no indication of any contamination in the oil.

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		HPL0004446	HPL0003010	HPL0001537
Sample Date		Client Info		22 Mar 2024	10 Sep 2023	10 Nov 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
Iron	ppm	ASTM D5185m	>200	109	74	54
Chromium	ppm	ASTM D5185m	>10	<1	<1	0
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		9	5	4
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	23	24	21
Lead	ppm	ASTM D5185m	>50	2	<1	0
Copper	ppm	ASTM D5185m	>200	4	4	3
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Silicon	ppm	ASTM D5185m	>50	4	3	1
Potassium	ppm	ASTM D5185m	>20	3	<1	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Sodium	ppm	ASTM D5185m		17	13	12
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m		1	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		2	3	2
Calcium	ppm	ASTM D5185m		51	44	40
Phosphorus	ppm	ASTM D5185m		592	556	522
Zinc	ppm	ASTM D5185m		38	33	14
Sulfur	ppm	ASTM D5185m		1130	1199	733
Acid Number (AN)	mg KOH/g	ASTM D8045		0.69	0.60	0.67
Visc @ 40°C	cSt	ASTM D445	220	222	219	220



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : HPL0004446

Lab Number : 06147516

Unique Number : 10977594

Test Package : MOB 2

Received : 12 Apr 2024

Tested : 15 Apr 2024

Diagnosed : 16 Apr 2024 - Don Baldrige

STEPAN - MILLSDALE PLANT

22500W. Millsdale Rd.

Elwood, IL

US 60421

Contact: Gregory Brooker

gbrooker@stepan.com

T: (815)774-5265

F: (815)774-5427

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)