



|                 |                 |
|-----------------|-----------------|
| WEAR            | <b>ABNORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b>   |
| FLUID CONDITION | <b>NORMAL</b>   |

Machine Id  
**JOHN DEERE 333G 1T0333GMLPF443874**

Component  
**Right Final Drive**  
Fluid  
**{not provided} (--- GAL)**

**RECOMMENDATION**

The oil change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|----------|----------|
| Sample Number  |     | Client Info |           | <b>JR0206250</b>   | ---      | ---      |
| Sample Date    |     | Client Info |           | <b>10 Apr 2024</b> | ---      | ---      |
| Machine Age    | hrs | Client Info |           | <b>451</b>         | ---      | ---      |
| Oil Age        | hrs | Client Info |           | <b>451</b>         | ---      | ---      |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | ---      | ---      |
| Oil Changed    |     | Client Info |           | <b>Changed</b>     | ---      | ---      |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | ---      | ---      |
| Sample Status  |     |             |           | <b>ABNORMAL</b>    | ---      | ---      |

**WEAR**

Gear wear is indicated. All other metal levels are typical for a new component breaking in.

|              |        |             |       |               |     |     |
|--------------|--------|-------------|-------|---------------|-----|-----|
| PQ           |        | ASTM D8184  | >1250 | <b>133</b>    | --- | --- |
| Iron         | ppm    | ASTM D5185m | >750  | <b>▲ 1884</b> | --- | --- |
| Chromium     | ppm    | ASTM D5185m | >9    | <b>▲ 27</b>   | --- | --- |
| Nickel       | ppm    | ASTM D5185m | >10   | <b>3</b>      | --- | --- |
| Titanium     | ppm    | ASTM D5185m |       | <b>0</b>      | --- | --- |
| Silver       | ppm    | ASTM D5185m |       | <b>0</b>      | --- | --- |
| Aluminum     | ppm    | ASTM D5185m | >40   | <b>6</b>      | --- | --- |
| Lead         | ppm    | ASTM D5185m | >15   | <b>0</b>      | --- | --- |
| Copper       | ppm    | ASTM D5185m | >40   | <b>4</b>      | --- | --- |
| Tin          | ppm    | ASTM D5185m | >10   | <b>0</b>      | --- | --- |
| Vanadium     | ppm    | ASTM D5185m |       | <b>0</b>      | --- | --- |
| White Metal  | scalar | *Visual     | NONE  | <b>LIGHT</b>  | --- | --- |
| Yellow Metal | scalar | *Visual     | NONE  | <b>NONE</b>   | --- | --- |

**CONTAMINATION**







There is no indication of any contamination in the oil.

|                  |        |             |        |              |     |     |
|------------------|--------|-------------|--------|--------------|-----|-----|
| Silicon          | ppm    | ASTM D5185m | >75    | <b>16</b>    | --- | --- |
| Potassium        | ppm    | ASTM D5185m | >20    | <b>33</b>    | --- | --- |
| Water            |        | WC Method   | >0.075 | <b>NEG</b>   | --- | --- |
| Silt             | scalar | *Visual     | NONE   | <b>NONE</b>  | --- | --- |
| Debris           | scalar | *Visual     | NONE   | <b>NONE</b>  | --- | --- |
| Sand/Dirt        | scalar | *Visual     | NONE   | <b>NONE</b>  | --- | --- |
| Appearance       | scalar | *Visual     | NORML  | <b>NORML</b> | --- | --- |
| Odor             | scalar | *Visual     | NORML  | <b>NORML</b> | --- | --- |
| Emulsified Water | scalar | *Visual     | >0.075 | <b>NEG</b>   | --- | --- |

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

|             |     |             |     |              |     |     |
|-------------|-----|-------------|-----|--------------|-----|-----|
| Sodium      | ppm | ASTM D5185m | >51 | <b>13</b>    | --- | --- |
| Boron       | ppm | ASTM D5185m |     | <b>1</b>     | --- | --- |
| Barium      | ppm | ASTM D5185m |     | <b>96</b>    | --- | --- |
| Molybdenum  | ppm | ASTM D5185m |     | <b>2</b>     | --- | --- |
| Manganese   | ppm | ASTM D5185m |     | <b>17</b>    | --- | --- |
| Magnesium   | ppm | ASTM D5185m |     | <b>4</b>     | --- | --- |
| Calcium     | ppm | ASTM D5185m |     | <b>21</b>    | --- | --- |
| Phosphorus  | ppm | ASTM D5185m |     | <b>255</b>   | --- | --- |
| Zinc        | ppm | ASTM D5185m |     | <b>4</b>     | --- | --- |
| Sulfur      | ppm | ASTM D5185m |     | <b>18131</b> | --- | --- |
| Visc @ 40°C | cSt | ASTM D445   |     | <b>144</b>   | --- | --- |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : JR0206250

Lab Number : 06147631

Unique Number : 10977709

Test Package : CONST ( Additional Tests: PQ )

Received : 12 Apr 2024

Tested : 15 Apr 2024

Diagnosed : 16 Apr 2024 - Don Baldrige

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**JRE - GREENSBORO**  
411 SOUTH REGIONAL ROAD  
GREENSBORO, NC  
US 27409

Contact: JUSTIN WILLIAMS  
justin.williams@jamesriverequipment.com

T: (336)668-2762

F: (336)665-9556