



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
GILLIG 346
 Component
Diesel Engine
 Fluid
TEXACO 15W40 (27 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0531227	WC0531190	WC0383290
Sample Date		Client Info		05 Apr 2024	28 Jan 2021	05 Oct 2020
Machine Age	mls	Client Info		333433	115720	92981
Oil Age	mls	Client Info		11332	11234	11336
Filter Age	mls	Client Info		11332	11234	11336
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	20	8	12
Chromium	ppm	ASTM D5185m	>5	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	<1	2	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>15	2	4	2
Lead	ppm	ASTM D5185m	>25	2	3	0
Copper	ppm	ASTM D5185m	>100	1	2	2
Tin	ppm	ASTM D5185m	>4	<1	7	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	9	7	8
Potassium	ppm	ASTM D5185m	>20	2	1	<1
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.8	0.2	0.4
Nitration	Abs/cm	*ASTM D7624	>20	9.4	8.5	9
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.1	21.1	22.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		3	2	2
Boron	ppm	ASTM D5185m		285	333	225
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		85	97	117
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		400	459	530
Calcium	ppm	ASTM D5185m		1445	1453	1370
Phosphorus	ppm	ASTM D5185m		1003	886	649
Zinc	ppm	ASTM D5185m		1198	1035	824
Sulfur	ppm	ASTM D5185m		3442	2362	2059
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.0	16.5	20.3
Base Number (BN)	mg KOH/g	ASTM D2896		6.5	7.5	7.1
Visc @ 100°C	cSt	ASTM D445	14.4	13.6	13.2	13.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0531227
Lab Number : 06147971
Unique Number : 10978049
Test Package : FLEET

Received : 12 Apr 2024
Tested : 15 Apr 2024
Diagnosed : 15 Apr 2024 - Wes Davis

LINK TRANSIT
 P.O. BOX 360, 2700 EUCLID 98801
 WENATCHEE, WA
 US 98807-0360
 Contact: JIM TIPPENS
 Jim@linktransit.com
 T: (509)664-7632
 F: (509)664-5130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)