



Area

(YA130683)

Machine Id

3703

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (8 GAL)

RECOMMENDATION

We advise that you check the fuel injection system. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0116382	GFL0098780	GFL0098786
Sample Date		Client Info		11 Apr 2024	01 Feb 2024	31 Oct 2023
Machine Age	hrs	Client Info		9961	9961	9961
Oil Age	hrs	Client Info		9961	9961	9961
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Changed	N/A
Filter Changed		Client Info		N/A	Changed	N/A
Sample Status				SEVERE	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	4	▲ 111	59
Chromium	ppm	ASTM D5185m	>5	<1	▲ 9	3
Nickel	ppm	ASTM D5185m	>4	<1	▲ 6	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	2	13	2
Lead	ppm	ASTM D5185m	>25	<1	4	0
Copper	ppm	ASTM D5185m	>100	<1	13	1
Tin	ppm	ASTM D5185m	>4	<1	2	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION









There is a high amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Silicon	ppm	ASTM D5185m	>25	3	11	6
Potassium	ppm	ASTM D5185m	>20	2	7	4
Fuel	%	ASTM D3524	>3.0	▲ 10.4	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.2	1.4	2.4
Nitration	Abs/cm	*ASTM D7624	>20	7.1	12.5	12.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.8	24.6	25.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

Sodium	ppm	ASTM D5185m		3	17	15
Boron	ppm	ASTM D5185m	0	8	5	13
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	53	65	69
Manganese	ppm	ASTM D5185m	0	<1	2	<1
Magnesium	ppm	ASTM D5185m	1010	780	957	1028
Calcium	ppm	ASTM D5185m	1070	1019	1068	1240
Phosphorus	ppm	ASTM D5185m	1150	928	974	1135
Zinc	ppm	ASTM D5185m	1270	1053	1241	1425
Sulfur	ppm	ASTM D5185m	2060	2929	2838	3296
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.0	22.1	20.0
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.4	7.0	6.7
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 10.5	12.9	14.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0116382 **Received** : 15 Apr 2024
Lab Number : 06148421 **Tested** : 17 Apr 2024
Unique Number : 10978499 **Diagnosed** : 17 Apr 2024 - Wes Davis
Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

GFL Environmental - 19DR - Deep Run/TriEast
 2287 Leslie R Stroud Road
 Kinston, NC
 US 28504-9477
 Contact: Spencer Ligon
 spencer.ligon@gflenv.com
 T: (800)207-6618
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)