



TRAAP

Texas Refinery Advanced Analysis Program

OIL ANALYSIS REPORT

WEAR	ABNORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
NORD-MAIN GEAR CLARIFIER 2
 Component
Gearbox
 Fluid
TRC 890 VARI-PURPOSE SAE80W90 (1 GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TR06148859	---	---
Sample Date		Client Info		04 Apr 2024	---	---
Machine Age	hrs	Client Info		27508	---	---
Oil Age	hrs	Client Info		8884	---	---
Filter Age	hrs	Client Info		0	---	---
Oil Changed		Client Info		Not Changd	---	---
Filter Changed		Client Info		Not Changd	---	---
Sample Status				ABNORMAL	---	---

WEAR

Gear wear is indicated. Bearing and/or bushing wear is indicated.

Iron	ppm	ASTM D5185m	>200	▲ 316	---	---
Chromium	ppm	ASTM D5185m	>10	4	---	---
Nickel	ppm	ASTM D5185m	>10	1	---	---
Titanium	ppm	ASTM D5185m		0	---	---
Silver	ppm	ASTM D5185m		0	---	---
Aluminum	ppm	ASTM D5185m	>25	0	---	---
Lead	ppm	ASTM D5185m	>50	22	---	---
Copper	ppm	ASTM D5185m	>200	▲ 264	---	---
Tin	ppm	ASTM D5185m	>10	▲ 19	---	---
Vanadium	ppm	ASTM D5185m		<1	---	---
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---

CONTAMINATION














There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	3	---	---
Potassium	ppm	ASTM D5185m	>20	2	---	---
Water	%	ASTM D6304	>0.2	0.137	---	---
ppm Water	ppm	ASTM D6304	>2000	1370	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	LIGHT	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	0.2%	---	---

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		0	---	---
Boron	ppm	ASTM D5185m		0	---	---
Barium	ppm	ASTM D5185m		0	---	---
Molybdenum	ppm	ASTM D5185m		0	---	---
Manganese	ppm	ASTM D5185m		2	---	---
Magnesium	ppm	ASTM D5185m		0	---	---
Calcium	ppm	ASTM D5185m		12	---	---
Phosphorus	ppm	ASTM D5185m	1000	587	---	---
Zinc	ppm	ASTM D5185m		22	---	---
Sulfur	ppm	ASTM D5185m	17000	19066	---	---
Acid Number (AN)	mg KOH/g	ASTM D8045		0.70	---	---
Visc @ 40°C	cSt	ASTM D445	207	172	---	---
Visc @ 100°C	cSt	ASTM D445	18	18.0	---	---
Viscosity Index (VI)	Scale	ASTM D2270	98	115	---	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TR06148859
Lab Number : 06148859
Unique Number : 10978937
Test Package : MOB 2 (Additional Tests: KF, KV100, VI)

CITY OF MCHENRY - KEVIN BEGGS
 1415 INDUSTRIAL DR
 MCHENRY, IL
 US 60050
 Contact: JERRY MORTON

To discuss this sample report, contact Customer Service at 1-800-827-0711.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: