



PacLease

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
857-3944
 Component
Diesel Engine
 Fluid
CHEVRON DELO 400 SAE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0014273	RPL0005600	---
Sample Date		Client Info		08 Mar 2024	08 Feb 2023	---
Machine Age	hrs	Client Info		10808	92160	---
Oil Age	hrs	Client Info		0	0	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		N/A	Changed	---
Filter Changed		Client Info		N/A	Changed	---
Sample Status				NORMAL	ABNORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	53	93	---
Chromium	ppm	ASTM D5185m	>20	2	4	---
Nickel	ppm	ASTM D5185m	>4	1	0	---
Titanium	ppm	ASTM D5185m		<1	0	---
Silver	ppm	ASTM D5185m	>3	0	0	---
Aluminum	ppm	ASTM D5185m	>20	7	44	---
Lead	ppm	ASTM D5185m	>40	<1	6	---
Copper	ppm	ASTM D5185m	>330	4	28	---
Tin	ppm	ASTM D5185m	>15	<1	2	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION









Test for glycol is negative. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	13	▲ 51	---
Potassium	ppm	ASTM D5185m	>20	42	150	---
Fuel		WC Method	>5	<1.0	<1.0	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol	%	*ASTM D2982		0.0	NEG	---
Soot %	%	*ASTM D7844	>3	0.7	0.3	---
Nitration	Abs/cm	*ASTM D7624	>20	12.6	11.6	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.2	24.1	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		25	6	---
Boron	ppm	ASTM D5185m		30	28	---
Barium	ppm	ASTM D5185m		1	0	---
Molybdenum	ppm	ASTM D5185m		14	12	---
Manganese	ppm	ASTM D5185m		1	7	---
Magnesium	ppm	ASTM D5185m		998	745	---
Calcium	ppm	ASTM D5185m		1823	1368	---
Phosphorus	ppm	ASTM D5185m	1260	997	684	---
Zinc	ppm	ASTM D5185m	1400	1151	861	---
Sulfur	ppm	ASTM D5185m		4475	2949	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.4	21.1	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	5.5	5.3	---
Visc @ 100°C	cSt	ASTM D445	11.1	10.8	11.5	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0014273 **Received** : 16 Apr 2024
Lab Number : 06149808 **Tested** : 17 Apr 2024
Unique Number : 10979886 **Diagnosed** : 18 Apr 2024 - Don Baldrige
Test Package : FLEET (Additional Tests: Glycol)

RTL PACLEASE - 7001 - Houston
 6300 N. Loop East
 Houston, TX
 US 77026
 Contact: RODNEY BRIGGS
 briggsr@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: