



PacLease

# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**857-5137**  
 Component  
**Diesel Engine**  
 Fluid  
**CHEVRON DELO 400 SAE 10W30 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>RPL0014520</b>	RPL0014063	RPL0010772
Sample Date		Client Info		<b>27 Mar 2024</b>	06 Dec 2023	07 Sep 2023
Machine Age	hrs	Client Info		<b>3560</b>	2689	27355
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	Changed
Filter Changed		Client Info		<b>N/A</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>36</b>	30	52
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	0	<1
Aluminum	ppm	ASTM D5185m	>20	<b>10</b>	14	59
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	0	1
Copper	ppm	ASTM D5185m	>330	<b>3</b>	4	10
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	2
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>15</b>	13	32
Potassium	ppm	ASTM D5185m	>20	<b>14</b>	29	143
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.4</b>	12.0	11.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.2</b>	23.2	24.2
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>2</b>	<1	5
Boron	ppm	ASTM D5185m		<b>31</b>	18	18
Barium	ppm	ASTM D5185m		<b>1</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>50</b>	37	9
Manganese	ppm	ASTM D5185m		<b>1</b>	0	2
Magnesium	ppm	ASTM D5185m		<b>530</b>	512	670
Calcium	ppm	ASTM D5185m		<b>1786</b>	1768	1347
Phosphorus	ppm	ASTM D5185m	1260	<b>888</b>	818	679
Zinc	ppm	ASTM D5185m	1400	<b>1021</b>	962	837
Sulfur	ppm	ASTM D5185m		<b>2933</b>	2797	2716
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>23.1</b>	24.5	20.8
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	<b>7.9</b>	6.2	4.8
Visc @ 100°C	cSt	ASTM D445	11.1	<b>11.5</b>	12.0	12.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : RPL0014520

Lab Number : 06149839

Unique Number : 10979917

Test Package : FLEET

Received : 16 Apr 2024

Tested : 17 Apr 2024

Diagnosed : 18 Apr 2024 - Don Baldrige

RTL PACLEASE - 7001 - Houston

6300 N. Loop East

Houston, TX

US 77026

Contact: RODNEY BRIGGS

briggs@rushenterprises.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)