



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |



Area  
**(63A3YA5)**  
Machine Id  
**411001-411001**  
Component  
**Diesel Engine**  
Fluid  
**CHEVRON DELO 400 MULTIGRADE 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>GFL0115776</b>  | GFL0103459  | GFL0103447  |
| Sample Date    |     | Client Info |           | <b>11 Apr 2024</b> | 21 Mar 2024 | 07 Feb 2024 |
| Machine Age    | hrs | Client Info |           | <b>8551</b>        | 8429        | 8182        |
| Oil Age        | hrs | Client Info |           | <b>751</b>         | 629         | 382         |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | 0           | 0           |
| Oil Changed    |     | Client Info |           | <b>N/A</b>         | N/A         | N/A         |
| Filter Changed |     | Client Info |           | <b>N/A</b>         | N/A         | N/A         |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >120 | <b>6</b>     | 2    | 3    |
| Chromium     | ppm    | ASTM D5185m | >20  | <b>&lt;1</b> | 0    | 0    |
| Nickel       | ppm    | ASTM D5185m | >15  | <b>&lt;1</b> | 0    | <1   |
| Titanium     | ppm    | ASTM D5185m | >2   | <b>0</b>     | 0    | 0    |
| Silver       | ppm    | ASTM D5185m | >3   | <b>0</b>     | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >20  | <b>2</b>     | 1    | 3    |
| Lead         | ppm    | ASTM D5185m | >40  | <b>&lt;1</b> | 0    | <1   |
| Copper       | ppm    | ASTM D5185m | >330 | <b>1</b>     | <1   | 2    |
| Tin          | ppm    | ASTM D5185m | >15  | <b>&lt;1</b> | 0    | <1   |
| Vanadium     | ppm    | ASTM D5185m |      | <b>&lt;1</b> | <1   | 0    |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

**CONTAMINATION**

There is no indication of any contamination in the oil.


|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >25   | <b>4</b>       | 3     | 4     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>19</b>      | 2     | 2     |
| Fuel             |          | WC Method   | >3.0  | <b>&lt;1.0</b> | <1.0  | <1.0  |
| Water            |          | WC Method   | >0.2  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >4    | <b>0.3</b>     | 0.2   | 0.3   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>7.4</b>     | 6.6   | 7.8   |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>18.4</b>    | 17.3  | 18.4  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.2  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |             |      |      |
|------------------|----------|-------------|------|-------------|------|------|
| Sodium           | ppm      | ASTM D5185m |      | <b>5</b>    | 6    | 3    |
| Boron            | ppm      | ASTM D5185m | 151  | <b>16</b>   | 16   | 22   |
| Barium           | ppm      | ASTM D5185m | 0.4  | <b>0</b>    | 0    | 0    |
| Molybdenum       | ppm      | ASTM D5185m | 250  | <b>70</b>   | 68   | 70   |
| Manganese        | ppm      | ASTM D5185m |      | <b>0</b>    | 0    | <1   |
| Magnesium        | ppm      | ASTM D5185m | 0    | <b>821</b>  | 848  | 797  |
| Calcium          | ppm      | ASTM D5185m | 2046 | <b>1087</b> | 1103 | 994  |
| Phosphorus       | ppm      | ASTM D5185m | 1043 | <b>930</b>  | 844  | 886  |
| Zinc             | ppm      | ASTM D5185m | 943  | <b>1090</b> | 1172 | 1105 |
| Sulfur           | ppm      | ASTM D5185m | 5012 | <b>3239</b> | 3372 | 2702 |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>14.2</b> | 13.5 | 14.4 |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 12.5 | <b>7.8</b>  | 8.1  | 7.7  |
| Visc @ 100°C     | cSt      | ASTM D445   | 14.4 | <b>12.8</b> | 12.9 | 12.9 |


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0115776  
**Lab Number** : 06150911  
**Unique Number** : 10980989  
**Test Package** : FLEET

**Received** : 16 Apr 2024  
**Tested** : 17 Apr 2024  
**Diagnosed** : 18 Apr 2024 - Sean Felton

**GFL Environmental - 180 - Tuscaloosa Hauling**  
 4701 12TH ST NE  
 Tuscaloosa, AL  
 US 35404

Contact: FREDERICK ROGERS  
 fred.rogers@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: