



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

Current

Machine Id

IC 13-23

Component

Front Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 10W30 (17 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0849372	---	---
Sample Date		Client Info		01 Mar 2024	---	---
Machine Age	mls	Client Info		12095	---	---
Oil Age	mls	Client Info		12095	---	---
Filter Age	mls	Client Info		12095	---	---
Oil Changed		Client Info		Changed	---	---
Filter Changed		Client Info		Changed	---	---
Sample Status				NORMAL	---	---

WEAR

Metal levels are typical for a components first oil change.

Iron	ppm	ASTM D5185m	>90	125	---	---
Chromium	ppm	ASTM D5185m	>20	2	---	---
Nickel	ppm	ASTM D5185m	>2	<1	---	---
Titanium	ppm	ASTM D5185m	>2	0	---	---
Silver	ppm	ASTM D5185m	>2	0	---	---
Aluminum	ppm	ASTM D5185m	>20	20	---	---
Lead	ppm	ASTM D5185m	>40	0	---	---
Copper	ppm	ASTM D5185m	>330	87	---	---
Tin	ppm	ASTM D5185m	>15	<1	---	---
Vanadium	ppm	ASTM D5185m		0	---	---
White Metal	scalar	*Visual	NONE	LIGHT	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---

CONTAMINATION












Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	33	---	---
Potassium	ppm	ASTM D5185m	>20	31	---	---
Fuel		WC Method	>3.0	<1.0	---	---
Water		WC Method	>0.2	NEG	---	---
Glycol		WC Method		NEG	---	---
Soot %	%	*ASTM D7844	>6	0.7	---	---
Nitration	Abs/cm	*ASTM D7624	>20	13.6	---	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.9	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		8	---	---
Boron	ppm	ASTM D5185m	250	23	---	---
Barium	ppm	ASTM D5185m	10	0	---	---
Molybdenum	ppm	ASTM D5185m	100	51	---	---
Manganese	ppm	ASTM D5185m		6	---	---
Magnesium	ppm	ASTM D5185m	450	761	---	---
Calcium	ppm	ASTM D5185m	3000	1279	---	---
Phosphorus	ppm	ASTM D5185m	1150	707	---	---
Zinc	ppm	ASTM D5185m	1350	880	---	---
Sulfur	ppm	ASTM D5185m	4250	2127	---	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.9	---	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	6.70	---	---
Visc @ 100°C	cSt	ASTM D445	10.9	11.6	---	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : WC0849372
 Lab Number : 06151293
 Unique Number : 10981371
 Test Package : MOB 2

Received : 16 Apr 2024
 Tested : 18 Apr 2024
 Diagnosed : 18 Apr 2024 - Wes Davis

INDIANOLA COMMUNITY SCHOOL DISTRICT
 1206 EAST ASHLAND, ATTN: JASON LOGAN
 INDIANOLA, IA
 US 50125
 Contact: JASON LOGAN
 loganj@indianola.k12.ia.us
 T: (515)961-9592
 F: (515)961-9504

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)