



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	ABNORMAL
FLUID CONDITION	NORMAL



Area
Mobile Fleet
 Machine Id
5227 5227
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (8 GAL)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0918963	WC0885933	WC0867126
Sample Date		Client Info		15 Apr 2024	25 Jan 2024	09 Nov 2023
Machine Age	hrs	Client Info		4815	4264	3716
Oil Age	hrs	Client Info		551	574	711
Filter Age	hrs	Client Info		551	574	711
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	24	28	29
Chromium	ppm	ASTM D5185m	>11	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	3	2	4
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	4	4	3
Lead	ppm	ASTM D5185m	>26	0	<1	0
Copper	ppm	ASTM D5185m	>26	3	2	1
Tin	ppm	ASTM D5185m	>4	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is a high amount of particulates present in the oil.

Silicon	ppm	ASTM D5185m	>22	6	11	12
Potassium	ppm	ASTM D5185m	>20	4	2	<1
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	0.5	0.8
Nitration	Abs/cm	*ASTM D7624	>20	7.1	8.6	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.7	21.8	22.5
Particles >4µm		ASTM D7647	>20000	▲ 38531	▲ 54364	▲ 44803
Particles >6µm		ASTM D7647	>5000	▲ 20990	▲ 29615	▲ 12207
Particles >14µm		ASTM D7647	>640	▲ 3572	▲ 5040	▲ 4154
Particles >21µm		ASTM D7647	>160	▲ 1203	▲ 1698	▲ 1399
Particles >38µm		ASTM D7647	>40	▲ 186	▲ 262	▲ 216
Particles >71µm		ASTM D7647	>10	▲ 19	▲ 27	11
Oil Cleanliness		ISO 4406 (c)	>21/19/16	▲ 22/22/19	▲ 23/22/20	▲ 23/21/19
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	2	2	1
Boron	ppm	ASTM D5185m		27	30	18
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		49	52	45
Manganese	ppm	ASTM D5185m		0	1	<1
Magnesium	ppm	ASTM D5185m		507	532	532
Calcium	ppm	ASTM D5185m		1767	1713	1683
Phosphorus	ppm	ASTM D5185m		855	807	784
Zinc	ppm	ASTM D5185m		987	953	970
Sulfur	ppm	ASTM D5185m		2696	2527	2505
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.7	21.5	20.6
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	9.9	8.8	9.7
Visc @ 100°C	cSt	ASTM D445	15.4	12.6	12.7	12.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0918963 **Received** : 17 Apr 2024
Lab Number : 06151847 **Tested** : 18 Apr 2024
Unique Number : 10981925 **Diagnosed** : 19 Apr 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PrtCount, TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CAROLINA SUNROCK
 PO BOX 25
 BUTNER, NC
 US 27509

Contact: Leigh Dennis
 rdennis@thesunrockgroup.com

T: (919)575-4505

F: (919)575-0162