



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**926030**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0116132</b>	GFL0116160	GFL0092619
Sample Date		Client Info		<b>12 Apr 2024</b>	20 Mar 2024	29 Nov 2023
Machine Age	hrs	Client Info		<b>21483</b>	21324	20784
Oil Age	hrs	Client Info		<b>159</b>	571	569
Filter Age	hrs	Client Info		<b>159</b>	571	569
Oil Changed		Client Info		<b>Changed</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Changed</b>	Changed	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>4</b>	9	8
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	0
Nickel	ppm	ASTM D5185m	>5	<b>1</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	7	4
Lead	ppm	ASTM D5185m	>40	<b>2</b>	2	1
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	2	2
Tin	ppm	ASTM D5185m	>15	<b>1</b>	1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>4</b>	4	4
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	18	9
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.1</b>	0.4	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.4</b>	8.5	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.0</b>	19.5	19.9
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	<1	2
Boron	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Barium	ppm	ASTM D5185m	0	<b>0</b>	1	0
Molybdenum	ppm	ASTM D5185m	60	<b>60</b>	64	58
Manganese	ppm	ASTM D5185m	0	<b>1</b>	<1	0
Magnesium	ppm	ASTM D5185m	1010	<b>970</b>	985	892
Calcium	ppm	ASTM D5185m	1070	<b>1072</b>	1201	1011
Phosphorus	ppm	ASTM D5185m	1150	<b>1164</b>	1126	1012
Zinc	ppm	ASTM D5185m	1270	<b>1270</b>	1312	1156
Sulfur	ppm	ASTM D5185m	2060	<b>3751</b>	3376	2910
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.1</b>	16.5	16.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.9</b>	7.1	7.2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.1</b>	13.1	13.0


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0116132  
**Lab Number** : 06152536  
**Unique Number** : 10982614  
**Test Package** : FLEET

**Received** : 17 Apr 2024  
**Tested** : 18 Apr 2024  
**Diagnosed** : 18 Apr 2024 - Wes Davis

**GFL Environmental - 947 - WB Horicon HC**  
 N7296 County Rd V  
 Horicon, WI  
 US 53032

Contact: Tim Kieffer  
 tim.kieffer@gflenv.com

T: (608)219-0288

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: