



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 324L 1LU324LHCZB068261
 Component
Rear Left Final Drive
 Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0209072	JR0167741	---
Sample Date		Client Info		16 Apr 2024	27 Apr 2023	---
Machine Age	hrs	Client Info		1311	543	---
Oil Age	hrs	Client Info		1311	543	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		Not Changed	Not Changed	---
Filter Changed		Client Info		Not Changed	None	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	191	176	---
Iron	ppm	ASTM D5185m	>750	492	405	---
Chromium	ppm	ASTM D5185m	>9	8	6	---
Nickel	ppm	ASTM D5185m	>10	1	<1	---
Titanium	ppm	ASTM D5185m		2	<1	---
Silver	ppm	ASTM D5185m		0	0	---
Aluminum	ppm	ASTM D5185m	>40	2	2	---
Lead	ppm	ASTM D5185m	>15	1	0	---
Copper	ppm	ASTM D5185m	>40	35	25	---
Tin	ppm	ASTM D5185m	>10	<1	0	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	MODER	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	43	42	---
Potassium	ppm	ASTM D5185m	>20	2	<1	---
Water		WC Method	>0.075	NEG	NEG	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	---

FLUID CONDITION

Confirm oil type. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	4	6	---
Boron	ppm	ASTM D5185m	6	140	119	---
Barium	ppm	ASTM D5185m	0	11	9	---
Molybdenum	ppm	ASTM D5185m	0	1	<1	---
Manganese	ppm	ASTM D5185m		7	5	---
Magnesium	ppm	ASTM D5185m	145	4	4	---
Calcium	ppm	ASTM D5185m	3570	789	789	---
Phosphorus	ppm	ASTM D5185m	1290	705	697	---
Zinc	ppm	ASTM D5185m	1640	1619	1594	---
Sulfur	ppm	ASTM D5185m		6613	7811	---
Visc @ 40°C	cSt	ASTM D445	57.0	79.5	79.3	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0209072 **Received** : 18 Apr 2024
Lab Number : 06153446 **Tested** : 19 Apr 2024
Unique Number : 10983524 **Diagnosed** : 22 Apr 2024 - Angela Borella
Test Package : CONST (Additional Tests: PQ)

JRE - GARNER
 4161 AUBURN CHURCH RD
 GARNER, NC
 US 27529

Contact: RALEIGH SHOP
 sean.betts@jamesriverequipment.com; catherine.anastasio@wearcheck.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)614-2260
 F: (919)779-5432