

#### WCLSNC Machine Id QC COOL ELC NC 09012022 Component Coolant

## CAT EXTENDED LIFE COOLANT (ELC) (--- GAL)

# RECOMMENDATION No corrective action is recommended at this time

No corrective action is recommended at this time. The fluid is suitable for further service.

### CORROSION

All metal levels are normal indicating no corrosion in the cooling system.

#### CONTAMINANTS


There is no indication of any contamination in the coolant.

. . . . . . . . . . .

## COOLANT CONDITION

Carboxylate test failed. Glycol and nitrite levels are acceptable. The pH level of this fluid is within the acceptable limits.

)						
Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0929342	WC0929341	WC0929340
Sample Date		Client Info		18 Apr 2024	17 Apr 2024	16 Apr 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
Iron	ppm	ASTM D6130	>2	<1	<1	<1
Aluminum	ppm	ASTM D6130	>2	0	0	0
Copper	ppm	ASTM D6130	>2	1	1	1
Lead	ppm	ASTM D6130	>2	<1	<1	<1
Tin	ppm	ASTM D6130	>2	0	0	0
Zinc	ppm	ASTM D6130	>10	0	0	0
Calcium	ppm	ASTM D6130	>5	0	0	0
Chlorine	ppm	ASTM D6130		2	6	0
Magnesium	ppm	ASTM D6130	>6	0	0	0
Total Dissolved Solids				388.0	334.0	320.0
Coolant Appearance		*Visual	Clear	normal	normal	normal
Boiling Point	°C	WC Method		225	225	225
Specific Gravity		*ASTM D1298		1.066	1.067	1.067
рН	Scale 0-14	ASTM D1287		8.26	8.20	8.19
Nitrites	ppm	AP-053:2009		976	712	864
Reserve Alkalinity	Scale 0-20	*ASTM D1121				
Percentage Glycol	%	ASTM D3321		49.1	49.3	49.3
Freezing Point	°F	ASTM D3321		-33	-33	-33
Carboxylate				fail	fail	fail
Silicon	ppm	ASTM D6130	0	<1	<1	1
Phosphorus	ppm	ASTM D6130	0	6	6	6
Boron	ppm	ASTM D6130	0	0	0	0
Molybdenum	ppm	ASTM D6130	950	741	700	674
Sodium	ppm	ASTM D6130		4061	3816	3738
Potassium	ppm	ASTM D6130		3	3	4
Coolant Color		*Visual		Red	Red	Red



Iron/Tin/Silver Reserve Alkalinity 10 13 12 10 0 serve Alkalinity mdd Abn Feb15/24 /lar26/24 Apr5/24 Jan31/24 Feb26/24 /ar19/24 Apr12/24 Mar26/24 Apr5/24 Aar5/74 Feb26/24 Mar19/24 Apr12/24 Mar5/7 Feb 15/2 Jan 31 Copper/Aluminum/Lead Freeze Point 10 10 -10 int (°C) -15 ppm reeze -20 -25 -30 -35 -40 -45 Feb15/24 Apr12/24 Jan31/24 Mar5/24 eh26/74 /ar19/24 Jan31/2 ar76/7 eb15/7 pН Nitrites 3000 2800 13 12 2600 2400 Ał 10 2200 2000 1800 itites 핌 1600 1400 1200 1000 800 600 400 0 200 Feb26/24 Apr5/24 Jan31/24 Apr12/24 Jan31/24 Mar19/24 Apr12/24 Feb 15/24 Feb 15/24 Mar5/74 Mar26/24 Feb26/24 Mar5/74 Mar19/24 unr5/24 Aar76/7

WEARCHECK LUBRICATION SERVICES QA ACCOUNT Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : WC0929342 Received : 18 Apr 2024 501 Madison Ave Lab Number : 06153567 Tested : 19 Apr 2024 Cary, NC Unique Number : 10983645 Diagnosed : 23 Apr 2024 - Jonathan Hester US 27513 Test Package : COOL- ( Additional Tests: BoilingPoint, COOL, GlycolType, ICP ) Contact: WCLS CARY NC Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (919)379-4102 F: (919)379-4050 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)