



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**JERRY A TINKEY**  
Machine Id  
[**JERRY A TINKEY**] 004 516506-4  
Component  
**Port Reduction Gear**  
Fluid  
**CHEVRON MEROPA 320 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0026940</b>	MW0063299	MW0046603
Sample Date		Client Info		<b>01 Apr 2024</b>	01 Dec 2023	01 Oct 2023
Machine Age	hrs	Client Info		<b>72101</b>	71777	71674
Oil Age	hrs	Client Info		<b>72101</b>	71777	71674
Filter Age	hrs	Client Info		<b>300</b>	71777	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>Changed</b>	Not Changd	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>155</b>	141	145
Chromium	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	0
Nickel	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	<1	0
Lead	ppm	ASTM D5185m	>100	<b>13</b>	10	11
Copper	ppm	ASTM D5185m	>50	<b>4</b>	3	2
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>2</b>	<1	<1
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	2	<1
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	5	4
Boron	ppm	ASTM D5185m	20	<b>26</b>	9	9
Barium	ppm	ASTM D5185m		<b>2</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>3</b>	0	<1
Manganese	ppm	ASTM D5185m		<b>2</b>	<1	<1
Magnesium	ppm	ASTM D5185m		<b>8</b>	6	<1
Calcium	ppm	ASTM D5185m	25	<b>157</b>	63	56
Phosphorus	ppm	ASTM D5185m	235	<b>266</b>	234	237
Zinc	ppm	ASTM D5185m		<b>37</b>	0	10
Sulfur	ppm	ASTM D5185m		<b>5061</b>	4853	4437
Acid Number (AN)	mg KOH/g	ASTM D8045	0.56	<b>0.72</b>	0.69	0.61
Visc @ 40°C	cSt	ASTM D445	304	<b>332</b>	330	332



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513

**Sample No.** : MW0026940

**Lab Number** : 06153807

**Unique Number** : 10989230

**Test Package** : MAR 2

**Received** : 18 Apr 2024

**Tested** : 20 Apr 2024

**Diagnosed** : 23 Apr 2024 - Jonathan Hester

**INGRAM BARGE**

900 S 3RD ST

PADUCAH, KY

US 42003

Contact: ZACH BURKHART

zachary.burkhart@ingrambarge.com

T:

F: (615)695-3697

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)