



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
ED OELTJEN [DANIEL/502899]
 Machine Id
VOLVO PENTA A444552
 Component
Port Diesel Engine
 Fluid
VOLVO PENTA SAE 15W40 (2 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA061947	VPA055432	VPA048247
Sample Date		Client Info		15 Apr 2024	27 Mar 2023	29 Mar 2022
Machine Age	hrs	Client Info		727	681	617
Oil Age	hrs	Client Info		0	87	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	74	67	74
Chromium	ppm	ASTM D5185m	>6	4	4	4
Nickel	ppm	ASTM D5185m	>2	3	3	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	2	<1
Aluminum	ppm	ASTM D5185m	>20	6	6	6
Lead	ppm	ASTM D5185m	>95	1	1	1
Copper	ppm	ASTM D5185m	>85	13	13	21
Tin	ppm	ASTM D5185m	>9	1	1	2
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	13	12	16
Potassium	ppm	ASTM D5185m	>20	4	3	4
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.5	0.5	0.8
Nitration	Abs/cm	*ASTM D7624	>20	7.0	7.1	8.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.3	20.5	22.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	3	0
Boron	ppm	ASTM D5185m		2	0	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		59	60	64
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		943	934	992
Calcium	ppm	ASTM D5185m		1079	1070	1127
Phosphorus	ppm	ASTM D5185m		1081	1038	1103
Zinc	ppm	ASTM D5185m		1267	1236	1323
Sulfur	ppm	ASTM D5185m		3407	2960	3063
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.9	15.0	17.0
Base Number (BN)	mg KOH/g	ASTM D2896		9.9	9.9	10.5
Visc @ 100°C	cSt	ASTM D445		13.5	13.6	13.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VPA061947 **Received** : 19 Apr 2024
Lab Number : 06154024 **Tested** : 22 Apr 2024
Unique Number : 10989447 **Diagnosed** : 23 Apr 2024 - Don Baldrige
Test Package : MOB 1 (Additional Tests: TBN)

Endor Marine LLC - Coastal Marine - 152124
 4300 11th Ave. NW
 SEATTLE, WA
 US 98107
 Contact: WILLOW YANARELLA
 service@coastalmarineengine.com
 T: (206)784-3703
 F: (206)784-8823

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)