



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**(EGX027)**  
Machine Id  
**2870**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (7 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0118013</b>	GFL0112308	GFL0112314
Sample Date		Client Info		<b>18 Apr 2024</b>	21 Feb 2024	14 Feb 2024
Machine Age	hrs	Client Info		<b>9137</b>	8858	8812
Oil Age	hrs	Client Info		<b>279</b>	325	279
Filter Age	hrs	Client Info		<b>279</b>	325	279
Oil Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	<b>10</b>	12	10
Chromium	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	3	3
Lead	ppm	ASTM D5185m	>150	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m	>90	<b>1</b>	4	3
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	<b>3</b>	0	3
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	3	5
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	<b>0.4</b>	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.7</b>	6.9	6.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.1</b>	18.3	17.3
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	11	3
Boron	ppm	ASTM D5185m	0	<b>8</b>	5	4
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>63</b>	59	55
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	0
Magnesium	ppm	ASTM D5185m	1010	<b>898</b>	851	838
Calcium	ppm	ASTM D5185m	1070	<b>1120</b>	1013	983
Phosphorus	ppm	ASTM D5185m	1150	<b>1002</b>	941	913
Zinc	ppm	ASTM D5185m	1270	<b>1164</b>	1116	1107
Sulfur	ppm	ASTM D5185m	2060	<b>3486</b>	2775	2779
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.2</b>	13.2	12.4
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.0</b>	7.7	7.6
Visc @ 100°C	cSt	ASTM D445	15.4	<b>12.8</b>	12.7	12.8



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0118013  
**Lab Number** : 06154073  
**Unique Number** : 10989496  
**Test Package** : FLEET

**GFL Environmental - 010 - Stockbridge**  
 1280 Rum Creek Parkway  
 Stockbridge, GA  
 US 30281  
 Contact: TECHNICIAN ACCOUNT  
 wcgfldemo@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)