



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	ATTENTION
FLUID CONDITION	ATTENTION

Area

Mobile Fleet

Machine Id

7091 7091

Component

Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 15W40 (--- QTS)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0919143	WC0919101	---
Sample Date		Client Info		16 Apr 2024	12 Apr 2024	---
Machine Age	hrs	Client Info		8867	8867	---
Oil Age	hrs	Client Info		8867	0	---
Filter Age	hrs	Client Info		8867	0	---
Oil Changed		Client Info		Changed	Not Changd	---
Filter Changed		Client Info		Changed	Not Changd	---
Sample Status				ATTENTION	ABNORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	7	5	---
Chromium	ppm	ASTM D5185m	>20	<1	<1	---
Nickel	ppm	ASTM D5185m	>4	0	0	---
Titanium	ppm	ASTM D5185m		0	0	---
Silver	ppm	ASTM D5185m	>3	0	0	---
Aluminum	ppm	ASTM D5185m	>20	3	2	---
Lead	ppm	ASTM D5185m	>40	<1	0	---
Copper	ppm	ASTM D5185m	>330	<1	<1	---
Tin	ppm	ASTM D5185m	>15	<1	1	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION











There is a moderate amount of particulates present in the oil.

Silicon	ppm	ASTM D5185m	>25	8	8	---
Potassium	ppm	ASTM D5185m	>20	2	3	---
Fuel		WC Method	>5	<1.0	1.2	---
Water		WC Method	>0.2	NEG	NEG	---
Glycol		WC Method		NEG	NEG	---
Soot %	%	*ASTM D7844	>3	0.1	0.1	---
Nitration	Abs/cm	*ASTM D7624	>20	7.0	6.8	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	15.9	15.3	---
Particles >4µm		ASTM D7647	>20000	11327	15686	---
Particles >6µm		ASTM D7647	>5000	6170	8545	---
Particles >14µm		ASTM D7647	>640	1050	1454	---
Particles >21µm		ASTM D7647	>160	354	490	---
Particles >38µm		ASTM D7647	>40	55	76	---
Particles >71µm		ASTM D7647	>10	6	8	---
Oil Cleanliness		ISO 4406 (c)	>21/19/16	21/20/17	21/20/18	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m	>158	0	<1	---
Boron	ppm	ASTM D5185m	250	12	12	---
Barium	ppm	ASTM D5185m	10	0	0	---
Molybdenum	ppm	ASTM D5185m	100	13	9	---
Manganese	ppm	ASTM D5185m		0	0	---
Magnesium	ppm	ASTM D5185m	450	125	93	---
Calcium	ppm	ASTM D5185m	3000	2858	2909	---
Phosphorus	ppm	ASTM D5185m	1150	1213	1110	---
Zinc	ppm	ASTM D5185m	1350	1395	1391	---
Sulfur	ppm	ASTM D5185m	4250	4190	4297	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.1	10.2	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	9.2	8.4	---
Visc @ 100°C	cSt	ASTM D445	14.4	12.0	12.0	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : WC0919143 Received : 19 Apr 2024
 Lab Number : 06154184 Tested : 23 Apr 2024
 Unique Number : 10989607 Diagnosed : 23 Apr 2024 - Don Baldrige
 Test Package : CONST (Additional Tests: PrtCount, TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CAROLINA SUNROCK

PO BOX 25
 BUTNER, NC
 US 27509

Contact: Leigh Dennis
 rdennis@thesunrockgroup.com

T: (919)575-4505
 F: (919)575-0162