



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[W66222]

Machine Id

JOHN DEERE 470 P 1FF470PAHPF000329

Component

Right Final Drive

Fluid

JOHN DEERE GL-5 80W90 (4 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W66222)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0206690	JR0193453	---
Sample Date		Client Info		17 Apr 2024	28 Nov 2023	---
Machine Age	hrs	Client Info		1091	553	---
Oil Age	hrs	Client Info		1091	553	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		Not Changd	Not Changd	---
Filter Changed		Client Info		N/A	N/A	---
Sample Status				NORMAL	NORMAL	---

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	31	2	---
Iron	ppm	ASTM D5185m	>750	154	10	---
Chromium	ppm	ASTM D5185m	>9	2	0	---
Nickel	ppm	ASTM D5185m	>10	0	0	---
Titanium	ppm	ASTM D5185m		<1	0	---
Silver	ppm	ASTM D5185m		0	0	---
Aluminum	ppm	ASTM D5185m	>40	0	<1	---
Lead	ppm	ASTM D5185m	>15	0	0	---
Copper	ppm	ASTM D5185m	>40	<1	0	---
Tin	ppm	ASTM D5185m	>10	<1	0	---
Vanadium	ppm	ASTM D5185m		<1	0	---
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>75	19	2	---
Potassium	ppm	ASTM D5185m	>20	<1	<1	---
Water		WC Method	>0.075	NEG	NEG	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	---

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	2	<1	---
Boron	ppm	ASTM D5185m		63	3	---
Barium	ppm	ASTM D5185m		2	0	---
Molybdenum	ppm	ASTM D5185m		0	0	---
Manganese	ppm	ASTM D5185m		4	<1	---
Magnesium	ppm	ASTM D5185m		0	11	---
Calcium	ppm	ASTM D5185m		18	15	---
Phosphorus	ppm	ASTM D5185m		479	329	---
Zinc	ppm	ASTM D5185m		0	0	---
Sulfur	ppm	ASTM D5185m		15769	18342	---
Visc @ 40°C	cSt	ASTM D445		190	142	---



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0206690 **Received** : 19 Apr 2024
Lab Number : 06154743 **Tested** : 22 Apr 2024
Unique Number : 10990166 **Diagnosed** : 23 Apr 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)