



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |



Machine Id

**VOLVO A45G 342398**

Component

**Brake Cooling System**

Fluid

**VOLVO SUPER WET BRAKE TRANSAXLE OIL WB102 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|----------|----------|
| Sample Number  |     | Client Info |           | <b>ML0001505</b>   | ---      | ---      |
| Sample Date    |     | Client Info |           | <b>15 Apr 2024</b> | ---      | ---      |
| Machine Age    | hrs | Client Info |           | <b>7441</b>        | ---      | ---      |
| Oil Age        | hrs | Client Info |           | <b>4000</b>        | ---      | ---      |
| Filter Age     | hrs | Client Info |           | <b>0</b>           | ---      | ---      |
| Oil Changed    |     | Client Info |           | <b>Changed</b>     | ---      | ---      |
| Filter Changed |     | Client Info |           | <b>Changed</b>     | ---      | ---      |
| Sample Status  |     |             |           | <b>NORMAL</b>      | ---      | ---      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |     |     |
|--------------|--------|-------------|------|--------------|-----|-----|
| Iron         | ppm    | ASTM D5185m | >50  | <b>4</b>     | --- | --- |
| Chromium     | ppm    | ASTM D5185m | >20  | <b>0</b>     | --- | --- |
| Nickel       | ppm    | ASTM D5185m | >10  | <b>0</b>     | --- | --- |
| Titanium     | ppm    | ASTM D5185m |      | <b>0</b>     | --- | --- |
| Silver       | ppm    | ASTM D5185m |      | <b>0</b>     | --- | --- |
| Aluminum     | ppm    | ASTM D5185m | >30  | <b>&lt;1</b> | --- | --- |
| Lead         | ppm    | ASTM D5185m | >50  | <b>0</b>     | --- | --- |
| Copper       | ppm    | ASTM D5185m | >200 | <b>20</b>    | --- | --- |
| Tin          | ppm    | ASTM D5185m | >20  | <b>0</b>     | --- | --- |
| Vanadium     | ppm    | ASTM D5185m |      | <b>0</b>     | --- | --- |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | --- | --- |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | --- | --- |

**CONTAMINATION**





There is no indication of any contamination in the oil.

|                  |        |             |       |              |     |     |
|------------------|--------|-------------|-------|--------------|-----|-----|
| Silicon          | ppm    | ASTM D5185m | >50   | <b>12</b>    | --- | --- |
| Potassium        | ppm    | ASTM D5185m | >20   | <b>0</b>     | --- | --- |
| Water            |        | WC Method   | >0.2  | <b>NEG</b>   | --- | --- |
| Silt             | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Debris           | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Sand/Dirt        | scalar | *Visual     | NONE  | <b>NONE</b>  | --- | --- |
| Appearance       | scalar | *Visual     | NORML | <b>NORML</b> | --- | --- |
| Odor             | scalar | *Visual     | NORML | <b>NORML</b> | --- | --- |
| Emulsified Water | scalar | *Visual     | >0.2  | <b>NEG</b>   | --- | --- |

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

|             |     |             |    |              |     |     |
|-------------|-----|-------------|----|--------------|-----|-----|
| Sodium      | ppm | ASTM D5185m |    | <b>1</b>     | --- | --- |
| Boron       | ppm | ASTM D5185m |    | <b>93</b>    | --- | --- |
| Barium      | ppm | ASTM D5185m |    | <b>0</b>     | --- | --- |
| Molybdenum  | ppm | ASTM D5185m |    | <b>0</b>     | --- | --- |
| Manganese   | ppm | ASTM D5185m |    | <b>&lt;1</b> | --- | --- |
| Magnesium   | ppm | ASTM D5185m |    | <b>&lt;1</b> | --- | --- |
| Calcium     | ppm | ASTM D5185m |    | <b>3627</b>  | --- | --- |
| Phosphorus  | ppm | ASTM D5185m |    | <b>1245</b>  | --- | --- |
| Zinc        | ppm | ASTM D5185m |    | <b>1498</b>  | --- | --- |
| Sulfur      | ppm | ASTM D5185m |    | <b>4686</b>  | --- | --- |
| Visc @ 40°C | cSt | ASTM D445   | 55 | <b>47.4</b>  | --- | --- |



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : ML0001505  
**Lab Number** : 06154966  
**Unique Number** : 10990389  
**Test Package** : CONST

**Received** : 19 Apr 2024  
**Tested** : 22 Apr 2024  
**Diagnosed** : 24 Apr 2024 - Jonathan Hester

**MCCLUNG-LOGAN EQUIPMENT CO - BALTIMORE**  
 4601 WASHINGTON BOULEVARD  
 BALTIMORE, MD  
 US 21227

Contact: MARK CIULLA  
 mciulla@mcclung-logan.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (410)242-6500  
 F: (410)242-7835