



PacLease

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
846-5247
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0019502	RPL0012338	RPL0007407
Sample Date		Client Info		01 Feb 2024	20 Aug 2023	11 May 2023
Machine Age	mls	Client Info		137482	126602	120762
Oil Age	mls	Client Info		10880	126602	6390
Filter Age	mls	Client Info		10880	0	6390
Oil Changed		Client Info		Changed	Changed	Filtered
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	38	79	56
Chromium	ppm	ASTM D5185m	>20	1	2	2
Nickel	ppm	ASTM D5185m	>4	0	<1	1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	<1
Aluminum	ppm	ASTM D5185m	>20	4	10	8
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	5	4	3
Tin	ppm	ASTM D5185m	>15	<1	<1	1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	10	14	12
Potassium	ppm	ASTM D5185m	>20	7	17	14
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.7	0.9	0.8
Nitration	Abs/cm	*ASTM D7624	>20	13.5	15.6	14.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.5	29.5	28.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		10	8	8
Boron	ppm	ASTM D5185m	0	8	30	27
Barium	ppm	ASTM D5185m	0	1	0	0
Molybdenum	ppm	ASTM D5185m	0	53	14	9
Manganese	ppm	ASTM D5185m		2	1	1
Magnesium	ppm	ASTM D5185m	0	924	822	747
Calcium	ppm	ASTM D5185m		1164	1396	1261
Phosphorus	ppm	ASTM D5185m		988	758	688
Zinc	ppm	ASTM D5185m		1178	925	827
Sulfur	ppm	ASTM D5185m		3480	3565	3359
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.9	33.7	31.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	6.0	4.2	4.3
Visc @ 100°C	cSt	ASTM D445	14	13.1	13.5	12.5


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : RPL0019502

Lab Number : 06155688

Unique Number : 10991111

Test Package : FLEET

Received : 22 Apr 2024

Tested : 23 Apr 2024

Diagnosed : 23 Apr 2024 - Wes Davis

RTL PACLEASE - 7011 - El Cajon

275 Vernon Way

El Cajon, CA

US 92020

Contact: Rudy Manager

TrevizoR@RushEnterprises.Com

T: (909)829-1044

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)