

## WEAR NORMAL CONTAMINATION NORMAL FLUID CONDITION NORMAL

Machine Id


24D1703 GL-120 Component New (Unused) Oil


{not provided} (--- GAL)

RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
This is a baseline read-out on the submitted sample.	Sample Number		Client Info		HPL006573		
	Sample Date		Client Info		18 Apr 2024		
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Filter Age	hrs	Client Info		0		
	Oil Changed		Client Info		N/A		
	Filter Changed		Client Info		N/A		
	Sample Status				NORMAL		
WEAR	lkon		ASTM D5185m		0		
	Iron	ppm			0		
	Chromium Nickel	ppm	ASTM D5185m ASTM D5185m		0		
		ppm			0		
	Titanium Silver	ppm	ASTM D5185m ASTM D5185m		0		
	Aluminum	ppm	ASTM D5185m				
	Lead	ppm	ASTM D5185m		<1 0		
	Copper	ppm	ASTM D5185m		0		
	Tin	ppm	ASTM D5185m		0		
	Vanadium	ppm ppm	ASTM D5185m		<1		
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
<u> </u>		·····	viouur	····			
CONTAMINATION	Silicon	ppm	ASTM D5185m		<1		
	Potassium	ppm	ASTM D5185m	>20	0		
	Water		WC Method		NEG		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
	Appearance	scalar	*Visual	NORML	NORML		
	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual		NEG		
FLUID CONDITION	Sodium	ppm	ASTM D5185m		<1		
	Boron	ppm	ASTM D5185m		0		
	Barium	ppm	ASTM D5185m		0		
	Molybdenum	ppm	ASTM D5185m		8		
	Manganese	ppm	ASTM D5185m		0		
	Magnesium	ppm	ASTM D5185m		0		
	Calcium	ppm	ASTM D5185m		3		
	Phosphorus	ppm	ASTM D5185m		184		
	Zinc	ppm	ASTM D5185m		<1		
	Sulfur	ppm	ASTM D5185m		23184		
	Acid Number (AN)	mg KOH/g	ASTM D8045		0.97		
	Visc @ 40°C	cSt	ASTM D445		216.4		
	Visc @ 100°C	cSt	ASTM D445		21.65		
						-	

Viscosity Index (VI) Scale ASTM D2270

119





Contact/Location: DAVID WARD - HIGMAN Page 2 of 2