

## WEAR NORMAL CONTAMINATION NORMAL FLUID CONDITION NORMAL

Machine Id

24D1104 HO-112 Component New (Unused) Oil

{not provided} (--- GAL)

	RECOMMENDATION	
--	----------------	--

This is a baseline read-out on the submitted sample.

WEAR

CONTAMINATION

## FLUID CONDITION

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		HPL006562		
Sample Date		Client Info		15 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Filter Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Filter Changed		Client Info		N/A		
Sample Status				NORMAL		
Iron	ppm	ASTM D5185m		0		
Chromium	ppm	ASTM D5185m		0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m		0		
Lead	ppm	ASTM D5185m		0		
Copper	ppm	ASTM D5185m		0		
Tin	ppm	ASTM D5185m		0		
Vanadium	ppm	ASTM D5185m		<1		
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
	304141	v13041				
Silicon	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	0		
Water	%	ASTM D6304		NEG		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual		NEG		
Sodium		ASTM D5185m		1		
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm ppm	ASTM D5185m		6		
Manganese		ASTM D5185m		0		
Magnesium	ppm ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		112		
Phosphorus	ppm	ASTM D5185m		862		
Zinc	ppm	ASTM D5185m		21		
Sulfur	ppm	ASTM D5185m		396		
Acid Number (AN)	mg KOH/g	ASTM D8045		2.533		
Visc @ 40°C	cSt	ASTM D445		4.21		
		ASTM D445		1.84		
Visc @ 100°C	cSt	A311VL1.1440		1.04		

Contact/Location: DAVID WARD - HIGMAN



